

# Plugin Series I

## Negative Ion + Ozone Technology

# OPERATING INSTRUCTIONS



NewAire Plugin units output negative ions and regulated amounts of ozone to eliminate odors and improve the air quality in rooms up to 500 sq. ft.

# newaire™



The NewAire Plugin is patented technology (Patent #5,316,741) wholly owned by: NewAire, Inc.  
9483 State Hwy. 37, Ogdensburg, NY 13669 • (315)393-5454 • [www.queenaire.com](http://www.queenaire.com)

# IMPORTANT

## **READ THIS INFORMATION BEFORE USING PRODUCT.**

NEVER operate this unit if it has a damaged plug, if it is not working properly, or if it has been damaged in any way. NEVER operate this unit with the air openings blocked in any way. Allow a minimum of 18 inches of clearance in front of the unit at all times. Keep the air openings free from lint, dust and the like. NEVER use outdoors.

### **⚠ WARNING!**

NEVER, under any circumstances, place any object into the unit via the air holes while the unit is plugged in as they may touch dangerous voltage points. Doing so could result in serious shock or create a fire hazard.

### **⚠ WARNING!**

ONLY plug this unit into a standard 120 VAC outlet. Under no circumstances whatsoever should any other power supply be used. A power supply with voltage greater than that specified for the unit can result in serious injury to the user. Voltages greater or significantly lower than that specified for the unit will result in irreparable damage to the unit and will void all warranties.

### **⚠ CAUTION! KEEP OUT OF REACH OF CHILDREN**

Under normal operating conditions the NewAire Plug In produces minimal amounts of ozone. The Canadian Standards Association (CSA) warns that concentrations above 0.04 ppm may be injurious to health.

# OPERATION

1. Read this pamphlet fully.
2. Plug into any 120 VAC grounded outlet – ideally mounted high and free from obstruction.
3. Turn on with the ON/OFF button. The green indicator light will glow steadily. The unit runs silently.
4. If the green light blinks, see cleaning instructions.
5. Arcing or snapping sounds may occur from humidity above 80% or entering particles.

## SPECIFICATIONS

Model	NAPLUGIN
Coverage Area	500 sq. ft.
Ozone Output	3 mg/hr
Negative Ion Output	750 cc/sec
Size	2.1"L 3.5"W 5.5"H
Weight	8.9 oz.
Volts / Hertz	120 / 60
Watts	3
Warranty	2 Years
ETL Listed	UL 867



**WARNING! SHOCK HAZARD. DO NOT OPEN.**

### AIR VENT

- Keep free of obstruction
- Preferably mount high
- Do not insert metal objects
- See cleaning instructions

### GREEN LIGHT INDICATOR

- Solid – operating properly
- Flashing – unplug immediately; needs cleaning or repair

### ON/OFF BUTTON



# CLEANING & MAINTENANCE



## **WARNING! DO NOT OPEN UNIT.**

Your NewAire Plugin requires no maintenance other than the occasional cleaning of the steel ring located behind the air hole openings. The frequency of cleaning is entirely dependent upon the amount of dust, lint or other airborne particles present when the unit is in use.

Cleaning this unit is necessary when the green indicator light flashes on or off while the unit is in operation. This flashing light indicates a build-up of dust/debris on the inner surface of the steel ring.

### **To clean your unit:**

1. ALWAYS turn the unit off by depressing the ON/OFF button and UNPLUG IT.
2. Sometimes dust or lint can be removed by blowing short breaths of air into the openings. If the green indicator light stops blinking, the cleaning was successful.
3. For more extensive cleaning, use a Q-tip dipped in rubbing alcohol. Insert into the center air hole and wipe the inside of the metal ring.
4. Plug in and turn on. If blinking continues, repeat step 2.
5. If repeated cleaning does not fix blinking, discontinue use and return the unit.
6. DO NOT attempt to service the unit – no user-serviceable parts.
7. To clean the exterior, use a dry or damp cloth. Never submerge the unit.

**FOR ADDITIONAL ASSISTANCE, CONTACT CUSTOMER SERVICE AT (877) 646-9663.**

# WARRANTY

## **The NewAire Plugin comes with a limited 2-year warranty as follows:**

1. Complete and return enclosed Warranty Card within 60 days of purchase. Failure to do so will render all warranty conditions null and void.
2. This unit is warranted against defects in material or workmanship for a period of two years from the date of proof of purchase. Any problems arising from misuse, attempt at repair, damage due to dropping, shipping or exposure to any liquid immediately render this warranty null and void.
3. If you have a warranty situation, contact NewAire customer service toll-free at (877) 646-9663.
4. NewAire, Inc. reserves the right to repair or replace any units which are covered under this warranty.
5. This warranty is in lieu of any and all other warranties, either expressed or implied. This includes, but is not limited to, implied warranties of merchantability or fitness for a particular purpose or function. In no event will NewAire be liable for any amount in excess of the original purchase price of the NewAire Plugin. No agent, dealer, distributor or service company is authorized to change, modify or extend terms of this warranty in any manner whatsoever.
6. This warranty gives specific legal rights. You may also have other rights which vary from state to state. This warranty is valid for units sold in the United States of America and Canada only.
7. NewAire Plugin is a patented product of NewAire, Inc.