

Green Seal Certification Standards

	<p>GS-37</p> <p>Bathroom, General and Glass Cleaners</p>	<p>GS-40</p> <p>Floor Strippers, Floor Finishes</p>
<p>Flammability/ Combustibility</p>	<p>The <i>undiluted</i> product shall not be combustible. The product shall have a flashpoint above 150°F.</p>	<p>The <i>undiluted</i> product shall not be combustible. The product shall have a flashpoint above 150°F.</p>
<p>Photochemical Smog. Tropospheric Ozone Production, and Indoor Air Quality</p>	<p>The product as used shall not contain substances that contribute significantly to the production of photochemical smog, tropospheric ozone or poor indoor air-quality. The volatile organic content of the product as used shall not exceed the following:</p> <ul style="list-style-type: none"> - 0.1% by weight for carpet cleaners - 1% by weight for general purpose & bath-room cleaners - 3% by weight for glass cleaner 	<p>The product as used shall not contain substances that contribute significantly to the production of photochemical smog, tropospheric ozone or poor indoor air-quality.</p> <ul style="list-style-type: none"> - 7% by weight for finishes - 3% by weight for strippers
<p>Toxicity to Aquatic Life</p>	<p>This product as used shall not be toxic to aquatic life. A compound is considered not toxic to aquatic life if it meets one or more of the following criteria: Acute LC₅₀ for algae, daphnia or fish >100 mg/L</p>	<p>Acute LC₅₀ for algae, daphnia or fish >100 mg/L</p>