

Absocold®
Compact Hotel All-Refrigerator
2.0 cu. ft. Auto-Defrost



SUITE FRIDGE® ARD204AB

- Stainless Door/
Black Cabinet**
Model: ARD204ABS
- Black**
Model: ARD204AB

KEY BENEFITS

- Fits most existing absorption-type unit cabinetry
- More energy and cooling efficient than absorption refrigerators
- Maintains 38° F at 78° F ambient temperature
- Special QUICK CHILL and SNOOZE Functions
- Environmentally safe
- Quiet Operation
- Commercial UL® listing

FEATURES

Energy	269 KWH/Yr Energy Consumption
Special Functions Control	Snooze Function (8 hours) Quick Chill Function (2 hours)
Defrost Type	Automatic Defrost
Door Type	Easy-Clean Euro-Round Door
Door Handle	Integrated Handle
Door-Swing	Reversible (Factory Standard, Right-Hand Hinge)
Interior Shelves	2 Full-Width Removable Glass Shelves
Door Storage	Beverage Can Dispenser (5 cans) 2 Door Shelves
Cabinet Design	Fits Most Existing Absorption Unit Cabinetry Clean-Back Design
Leveling	2 Front Adjustable Leveling Feet
Capacity	2.0 cu. ft. Total Capacity

DIMENSIONS

Height	22 3/8 in.
Width	18 1/2 in.
Depth	19 in.
Weight	42 lbs.
Carton Height	23 1/2 in.
Carton Width	21 in.
Carton Depth	20 in.
Shipping Weight	46 lbs.
Shipping Cube	5.7 cu. ft.

ELECTRICAL

A minimum 15 AMP electrical supply is required (20 AMP electrical supply preferred). A time-delay fuse or circuit breaker and separate circuit is recommended. 115V., 60 Hz.

Start-up Amperage: 3.6 AMPS
Running Amperage: 0.9 AMPS



ARD204ABS



ARD204AB



Listed by
Underwriters
Laboratories.

Product specifications subject to change without notice

Absocold Corporation, P.O. Box 1545, Richmond, IN 47375
Toll-Free: 800-843-3714 • Fax: 765-935-3450
www.absocold.com • absocold@absocold.com