

Absocold® ENERGY STAR® Qualified Compact All-Refrigerator 2.3 cu. ft. Single-Door - Auto-Defrost



ARD244A



Black

Model: ARD244AB10R/L



White

Model: ARD244AW10R/L



FEATURES

Energy	ENERGY STAR® Qualified - Tier III 223 KWH/Yr Energy Consumption 20% less energy than Federal Standard
Defrost Type	Automatic Defrost
Refrigerant Type	Non-Flammable R134A
Foaming Agent Type	Non-Flammable 245F
Temperature Control	Full Range Control
Door Type	Easy-Clean Euro-Round Door
Door Handle	Integrated Handle
Door-Swing	Reversible (Factory Standard, Right-Hand Hinge)
Interior Shelves	2 Full-Width Adjustable Wire Shelves
Door Storage	2 Full-Width Shelves Lower Shelf accepts 2-Liter Bottles
Leveling	2 Front Adjustable Leveling Feet
Capacity	2.28 cu. ft. Total Capacity

INSTALLATION REQUIREMENTS

Remove all packing material and tape. Install on a level floor or well-supported counter. Avoid any direct sunlight, heat source, or moisture. This product is designed to be *freestanding* and must be installed at least 2" from the wall, and the cabinet bottom is at least 3/4" to 1" above the floor or carpet, in order to let the air circulate freely around the unit.

DIMENSIONS

Height	25 in.
Width	18 1/2 in.
Depth	20 in.
Weight	39 lbs.
Carton Height	26 5/8 in.
Carton Width	20 1/4 in.
Carton Depth	23 3/4 in.
Shipping Weight	44 lbs.
Shipping Cube	7.2 cu. ft.

ELECTRICAL

A minimum 15 AMP electrical supply is required (20 AMP electrical supply preferred). A time-delay fuse or circuit breaker and separate circuit is recommended. 115V, 60 Hz.

Running Amperage: 0.8 AMPS

Product specifications subject to change without notice



Listed by
Underwriters
Laboratories.

Absocold, P.O. Box 1545, Richmond, IN 47375 Toll-Free: 800-843-3714 • Fax: 765-935-3450
www.absocold.com • absocold@absocold.com