Pro:Centric Hospitality TV with Pro:Idiom and Embedded b-LAN

LT570H(NA)

The LT570H Series features reliable FHD resolution that creates crystal clear pictures. It has LG Pro:Centric technology, which offers easy tools for partners to create interactive applications with increased visual appeal. These features enable delivery of a wide range of unique experiences tailored to both hotel management and guests' needs.





Pro:Centric V HOTEL MANAGEMENT SOLUTION

Pro:Centric provides comprehensive solutions in RF infrastructure. Through the Pro:Centric server and app, hoteliers are able to customize their settings and deliver information on hotel facilities and wake-up call services, weather forecasts and other guest messages, all while reinforcing the hotel's brand image.

Dozens of Languages

This series supports 39 languages (including Hebrew, Arabic and Farsi) and language alignment, making guests from around the world feel more at home and comfortable.

Basic & Easy Templates

Pro:Centric Application (PCA) provides basic, easy-to-use templates that can be selected based on customer preference.

Customizable Template & Page

Choose alternative looks for billboards based on your preferences, and edit multiple sections with up to 40 pages of billboards by yourself with this web-based tool.

Multi-Channel Spooling

Operation of up to eight hotel channels (22 sub-channels) offers programming flexibility, customized content and additional services.



Right Alignment (Hebrew, Arabic, Farsi)



Left Alignment (36 languages)



Welcome image of PCA





HOSPITALITY FEATURES

Pro:Idiom

DRM (Digital Right Management) technology unlocks access to premium content to help assure rapid and broad deployment of HDTV and other high value digital contents.



Commercial Swivel Stand

The LT570H commercial grade stand swivels to allow guests to view the TV from virtually any angle and can easily be fastened to a tabletop for security purposes.



HOSPITALITY FEATURES

Self Diagnostics via USB

Enables service engineers to recognize technical issues in a TV quickly and easily through a USB. The TV stores any technical issues encountered and can output them to a USB device. Service engineers use this information to analyze technical issues without the actual TV.

USB Data Cloning

USB data cloning makes managing multiple displays more efficient for optimal operation. No need to set up each display one by one, data can be copied to a USB in one display, data will be distributed to other displays through a USB plug-in.

EzManger

EzManager provides a convenient installation function to automatically set settings for the Pro:Centric TV without any extra configuration. Auto-installation requires 1~3 minutes, while manual installation requires 3~5 minutes.





| | Processing Pro:Centric Configuration Step 2 may take up to 30 min(s) | |
|------|---|--|
| | Please wait | |
| - | | |
| Step | | |
| | 3 Searching for the network type | |
| | 4 Searching for the network type | |
| | 5 Searching for the network type | |
| Step | 6 Searching for the network type | |

HOSPITALITY FEATURES

Welcome Screen

Display a warm greeting message with your hotel name and logo on the TV when it is turned on. The welcome screen provides an inviting, personalized experience for your guests.

Multi IR

Multi-code IR function eliminates any remote control signal interference between TVs in rooms with multiple TVs installed.

External Speaker Out

Enhance the entertainment experience with an additional speaker (sold separately). Guests can listen to the TV audio from other rooms within their suite, not only the room where the TV is located.







DIMENSION



32H"



CONNECTIVITY

49" / 43"



32H"



* Dimensions & Jack Panels (Read/Side) may differ from the above image, so please contact LG sales team to verify before ordering.

SPECIFICATIONS

| | | 49LT570H | 43LT570H | 32LT570H | |
|-------------------------------|---|--|-------------------------------------|-------------------------------------|--|
| CATEGORY | Category | Pro:Centric V | Pro:Centric V | Pro:Centric V | |
| DESIGN | Stand Type | 1 pole (Swivel) | 1 pole (Swivel) | 1 pole (Swivel) | |
| | Front Color | Ceramic BK (PCM : Pre-coated Metal) | Ceramic BK (PCM : Pre-coated Metal) | Ceramic BK (PCM : Pre-coated Metal) | |
| DISPLAY | Inch | 49" | 43" | 32H" | |
| | Resolution | 1,920 x 1,080 (FHD) | 1,920 x 1,080 (FHD) | 1,366 x 768 (HD) | |
| | Backlight Unit Type | Direct BLU | Direct BLU | Direct BLU | |
| | Brightness (cd/m ²) | 400 | 400 | 240 | |
| BROADCASTING SYSTEM | TV Reception | ATSC (QAM / VSB), Analog NTSC | ATSC (QAM / VSB), Analog NTSC | ATSC (QAM / VSB), Analog NTSC | |
| VIDEO | HDR / HDR Dolby Vision | No / No | No / No | No / No | |
| AUDIO | Audio Output | 10W + 10W | 10W + 10W | 5W + 5W | |
| | Speaker System | 2.0 ch | 2.0 ch | 2.0 ch | |
| HOSPITALITY SOLUTION | Solution Type | Pro:Centric (V) | Pro:Centric (V) | Pro:Centric (V) | |
| | Pro:Centric Smart | No | No | No | |
| | Data Streaming (IP & RF) | No | No | No | |
| | HCAP (GEM / FLASH / HTML) ※ Service Carousel (TLL / XML) | GEM | GEM | GEM | |
| | Pro:Centric Server | PCS400R | PCS400R | PCS400R | |
| | DRM | Pro:ldiom (H/W Type) | Pro:Idiom (H/W Type) | Pro:Idiom (H/W Type) | |
| HOSPITALITY FEATURES | | b-LAN embedded, EzManager (Simplicity), USB Cloning, Diagnostics (USB), TVLink Interactive(RS-232C, MPI), HTNG-CEC (1.4), Simplink (HDMI-CEC, 1.4), IR Out, Multi IR Code, PDM (Installer Menu), Welcome Screen, Insert Image, One Channel Map, External Speaker Out, Instant ON, RJP (Remote Jack Pack) Compatibility, Auto Off / Sleep Timer, Motion Eye Care, Anti-theft System (Kensington Lock, Credenza / Security Screw Hole, Lock Down Plate), Chromecast Dongle Anti-theft Cover (Optional, 49" only) | | | |
| JACK INTERFACE | Set Side | HDMI In 1.4 (2), USB 2.0, | | | |
| | Set Rear | HDMI In (HDCP) - 1.4, RF In (Single b-LAN), AV In (RCA3 Type), Digital Audio Out (Optical), PC Audio Input (Share with Composite Audio), RS-232C (Control & Service), RJ45 (RJP Interface, Pro:Centric), External Speaker Out (3.5mm Phone Jack, Spk-out & Line Out), MPI Port (RJ12 jack), Debug (Phone Jack Type, CPU/PTC), TV link Configuration (Phone Jack Type, b_LAN Service) | | | |
| DIMENSION (UNIT : mm / kg) | Vesa | 300 × 300 | 200 x 200 | 200 x 200 | |
| | W x H x D / Weight (with stand) | 1,110 x 705 x 303 / 14.5 | 977 x 630 x 303 / 11.2 | 739 x 495 x 241 / 6.05 | |
| | W x H x D / Weight (without stand) | 1,110 x 650 x 72 (81.1) / 11.3 | 977 x 575 x 71.7 (80.8) / 8.0 | 739 x 441 x 74.6 (84) / 4.85 | |
| | W x H x D / Weight (Shipping) | 1,296 x 770 x 171 / 17.2 | 1,147 x 660 x 175 / 13.9 | 905 x 530 x 162 / 7.35 | |
| POWER (UNIT : WATTS) | Voltage, Hz | 120, 50/60 | 120, 50/60 | 120, 50/60 | |
| | Typical | 79.1W | 60.0W | 36.5W | |
| | Stand-by | Under 0.5W | Under 0.5W | Under 0.5W | |

* Specifications are subject to change without notice, so please contact LG sales team to verify before ordering.



www.lg.com/b2b
www.youtube.com/c/LGECommercialDisplay
www.facebook.com/LGInformationDisplay
www.linkedin.com/company/LGInformationDisplay

LG may make changes to specifications and product descriptions without notice. Copyright © 2019 LG Electronics Inc. All rights reserved. "LG Life's Good" is a registered trademark of LG Corp. The names of products and brands mentioned here may be the trademarks of their respective owners.

