



Small is the new big!
Amazingly big on features, yet surprisingly small in size.

SMALL IS THE NEW BIG!

Available in single and two-line, analog, VoIP, corded, and cordless configurations, micro-footprint Teledex E Series phones have created an entirely new hotel guest room telephone category. Originally designed to meet the limited space requirements aboard cruise ships, E Series phones require less room on the hotel guest room desk and nightstand, and consume less energy in the manufacturing process, so the impact on the environment is smaller as well.

- Single or two-line speakerphones
- Patented OneTouch voice mail retrieval
- Dual Neon/LED message-waiting light
- Electronic 3-way conference (two-line models)
- LED indicator lights for Speaker, Mute, & Hold keys, Line 1 & Line 2 keys (2-line models only)
- Available in Ash or Black

E Series VoIP Corded

- Up to seven (7) configurable Guest Service Keys
- LCD display with digital clock screen
- Dual Port (10/100) for HSIA
- ETrim available

E Series Analog Corded

- Eight (8) configurable Guest Service Keys
- EasyAccess™ data port
- ETrim available

E Series VoIP Cordless

- Available Frequencies: 1.8 GHz and 1.9 GHz
- Supports up to four handsets, including one on the base and three remotes
- Up to seven (7) configurable Guest Service Keys
- HAC/VCH (ADA) compliant handset volume boost
- Dual Port (10/100) for HSIA
- RediDock available

E Series Analog Cordless

- Available frequencies: 1.8 GHz and 1.9 GHz
- Supports up to four handsets, including one on the base and three remotes
- Eight (8) configurable Guest Service Keys
- HAC/VCH (ADA) compliant handset volume boost
- EasyAccess™ data port
- RediDock available



RediDock available.

E SERIES VOIP SPECIFICATIONS

Standard Colors:	Ash and Black
Footprint (Desk):	4.5" (11.43cm) (w) x 8" (20.32cm) (l) x 3.63" (9.22cm) (d) (max height with desk stand)
Footprint (Wall):	4.5" (11.43cm) (w) x 8" (20.32cm) (l) x 1.5" (3.81cm) (d) (depth from wall mount)
Weight:	2.0 lbs. (900g)
Weight (ETrim/RediDock):	12oz. (340g)
Frequency (cordless):	1.9GHz or 1.8GHz
Power:	Power over Ethernet (POE) 802.3af Compliant
Power (cordless):	Remote charging station includes Handset w/ Battery & AC Adapter
Standby Time (cordless):	10 days
Talk Time (cordless):	6 hours
Range (cordless):	100ft (30m)
Humidity:	65% ± 20%
Temperature:	77°F ± 50° (25°C ± 10°C)
FCC Specifications:	FCC Part 15 Support B: 2009
Safety Standard:	UL - 60950-1 2nd edition ADA/HAC
RFCs:	3261 (SIP), 3842 (SIP Subscribe), 2833 (SIP Info)
Handset Coil-Cord:	10 ft (3.048m)
Line Cord:	RJ14 line cord - 12 ft (3.66m)
Line Cord (cordless):	RJ45 Line Cord - 12ft (3.66m)
Packaging:	10 per carton
Packaging (RediDock):	20 per carton



Features and specifications are subject to change without notice.
The values for mass and dimension are approximate.

PART NUMBERS

VOIP CORDLESS 1.9GHZ

E103 - 4GSK 1.9GHz, 1L, MW, Spkr	EA011319S04D
E103 - 8GSK 1.9GHz, 1L, MW, Spkr	EA011319S08D
E103 - RediDock 1.9GHz, 1L, RediDock	EA11319S0HKU
E203 - 4GSK 1.9GHz, 2L, MW, Spkr	EA012319S04D
E203 - 8GSK 1.9GHz, 2L, MW, Spkr	EA012319S08D
E203 - RediDock 1.9GHz, 1L, RediDock	EA12319S0HKU

VOIP CORDED

E100IP - Lobby 1L, Lobby	EV10N0L3
E100IP - Basic 1L, Basic, Spkr	EV011000S00T3
E100IP - 4GSK 1L, MW, Spkr	EV110S4D3
E100IP - 7GSK 1L, MW, Spkr	EV110S7D3
E100IP - ETrim 1L, Trimline	EV110N0T3
E200IP - Basic 2L, Basic, Spkr	EV012000S00T3
E200IP - 4GSK 2L, MW, Spkr	EV120S4D3
E200IP - 7GSK 2L, MW, Spkr	EV120S7D3
E200IP - ETrim 2L, Trimline	EV120N0T3

PACKAGE CONTENTS

- Handset
- Base Unit
- AC Adapter
- 10' foot Handset Coil Cord
- 12' 4-wire RJ-14 Line Cord
- Fixed Plastic Template



E SERIES ANALOG SPECIFICATIONS

Standard Colors:	Ash and Black
Footprint (Desk):	4.5" (11.43cm) (w) x 8" (20.32cm) (l) x 3.63" (9.22cm) (d) (max height with desk stand)
Footprint (Wall):	4.5" (11.43cm) (w) x 8" (20.32cm) (l) x 1.5" (3.81cm) (d) (depth from wall mount)
Weight:	1.4 lbs. (0.64kg)
Weight (ETrim/RediDock):	10oz. (290g)
Frequency (cordless):	1.9GHz or 1.8GHz
Power:	Wall Adapter
Power (cordless):	Remote charging station includes Handset w/ Battery & AC Adapter
Standby Time (cordless):	10 days
Talk Time (cordless):	6 hours
Range (cordless):	100ft (30m)
Humidity:	65% ± 20%
Temperature:	77°F ± 50° (25°C ± 10°C)
FCC Specifications:	Meets or exceeds Part 68, FCC Part 15 & UL 1459 Ref.
Safety Standard:	UL - 60950-1 2nd edition ADA/HAC
Operating Voltage:	324-56 VDC Non-Polarity
Flash Timing:	600ms
Ringer Equivalence:	Z (Use only behind PBX)
Handset Coil-Cord:	10 ft (3.048m)
Line Cord:	RJ14 line cord - 12 ft (3.66m)
Line Cord (cordless):	RJ45 Line Cord - 12ft (3.66m)
Faceplate Size:	Full Length
Packaging:	10 per carton
Packaging (RediDock):	20 per carton



Features and specifications are subject to change without notice.
The values for mass and dimension are approximate.

PART NUMBERS

ANALOG CORDLESS 1.9GHZ

E103 - 4GSK 1.9GHz, 1L, MW, Spkr	EV011319S07D
E103 - 8GSK 1.9GHz, 1L, MW, Spkr	EA011319S08D
E103 - RediDock 1.9GHz, 1L, RediDock	EV011319S00H
E203 - 4GSK 1.9GHz, 2L, MW, Spkr	EV012319S04D
E203 - 8GSK 1.9GHz, 2L, MW, Spkr	EV012319S07D
E203 - RediDock 1.9GHz, 1L, RediDock	EV012319S00H

ANALOG CORDLESS 1.8GHZ

E103 - 4GSK 1.8GHz, 1L, MW, Spkr	EA011319S04D
E103 - 8GSK 1.8GHz, 1L, MW, Spkr	EA011319S08D
E103 - RediDock 1.8GHz, 1L, RediDock	EA011319S00H
E203 - 4GSK 1.8GHz, 2L, MW, Spkr	EA012319S04D
E203 - 8GSK 1.8GHz, 2L, MW, Spkr	EA012319S08D
E203 - RediDock 1.8GHz, 1L, RediDock	EA012319S00H

ANALOG CORDED

E100 8GSK 1L, MW, Spkr Black	EA011000S08D
E100 4GSK 1L, MW, Spkr Black	EA011000S04D
E100 ETrim 1L, Trimline Black	EA011000S00T
E100 Lobby 1L, Lobby Black	EA011000N00L
E200 2L, MW, Spkr Black	EA012000S08D
E200 2L, MW, Spkr Black	EA012000S04D
E200 Trimline 2L, Black	EA012000S00T
E200IP - ETrim 2L, Trimline	EV120N0T3

PACKAGE CONTENTS

- Handset
- Base Unit
- AC Adapter
- 10' foot Handset Coil Cord
- 12' 4-wire RJ-14 Line Cord
- Fixed Plastic Template



Cetis 
Telemed • TeleMatrix • Scitec

Cetis, Inc.
4975 N. 30th Street
Colorado Springs, CO
80919 USA
☎ +1.719.638.8821
✉ +1.719.638.8815
info@cetis.com

Cetis.com

 @CetisGroup

© 2018 Cetis, Inc. Product specifications and descriptions in this document subject to change without notice. Cetis®, Telemed®, TeleMatrix®, and Scitec® are trademarks or registered trademarks of Cetis, Inc.

TDX-M-DS-112018