SUMMIT

CR2B121



3.25" x 21.25" x 18" (H x W x D)

2-burner 120V electric cooktop designed for portrait or landscape installation, with smooth black ceramic glass surface

Highlights:

Innovative design allows the cooktop to be mounted in portrait or landscape style to accommodate any setup

Fits popular 20" x 16" counter cutouts

Two-burner electric cooktop with 120V operation

Product Features:

| Versatile placement | Specially designed to be mounted portrait or landscape style with controls being easy to read and manage in either direction |
|------------------------------|--|
| Smooth black ceramic surface | Easy cleanup and elegant style on a smooth ceramic glass surface |
| Fits popular cutout size | Designed for built-in installation in 20" x 16" cutouts |
| Two heating elements | One 900W 7" burner and one 500W 5 1/2" burner in smooth ceramic glass |
| 115V operation | Designed to work with standard 115V/60Hz electrical supplies with proper grounding |
| Push-to-turn knobs | Prevents accidents by requiring a small amount of force to turn on cooktop heat |
| Residual heat indicator | Indicator will illuminate to warn if some part of the glass surface is too hot to touch |
| Indicator lights | Operating indicators light up to show which burner is in use |
| Cord included | Ships with 3-pronged cord |



SUMMIT

CR2B121 Specifications:

| Height of Cabinet3.25" (8 cmWidth21.25" (54 cmDepth18.0" (46 cmCabinetBlaUS Electrical SafetyETCanadian Electrical SafetyETLAmps200Voltage/Frequency115 V AC/60 HWeight18.0 lbs. (8 kmShipping Weight25.0 lbs. (11 kmParts & Labor Warranty1 YemElectric Cooktop100 | m) m) ck TL -C 0.0 Hz |
|---|---|
| Depth18.0" (46 crCabinetBlaUS Electrical SafetyECanadian Electrical SafetyETLAmps20Voltage/Frequency115 V AC/60 HWeight18.0 lbs. (8 kShipping Weight25.0 lbs. (11 kParts & Labor Warranty1 Ye | m) ck TL -C .0 Hz |
| CabinetBlaUS Electrical SafetyECanadian Electrical SafetyETLAmps20Voltage/Frequency115 V AC/60 HWeight18.0 lbs. (8 kShipping Weight25.0 lbs. (11 kParts & Labor Warranty1 Ye | ck TL -C 0.0 Hz |
| US Electrical SafetyETCanadian Electrical SafetyETLAmps20Voltage/Frequency115 V AC/60 HWeight18.0 lbs. (8 kShipping Weight25.0 lbs. (11 kParts & Labor Warranty1 Ye | -C 0.0 |
| Canadian Electrical SafetyETLAmps20Voltage/Frequency115 V AC/60 HWeight18.0 lbs. (8 kShipping Weight25.0 lbs. (11 kParts & Labor Warranty1 Ye | -C 0.0 Hz |
| Amps20Voltage/Frequency115 V AC/60 FWeight18.0 lbs. (8 kShipping Weight25.0 lbs. (11 kParts & Labor Warranty1 Ye | 0.0 Hz |
| Voltage/Frequency115 V AC/60 HWeight18.0 lbs. (8 kShipping Weight25.0 lbs. (11 kParts & Labor Warranty1 Ye | Ηz |
| Weight18.0 lbs. (8 kShipping Weight25.0 lbs. (11 kParts & Labor Warranty1 Ye | |
| Shipping Weight25.0 lbs. (11 kParts & Labor Warranty1 Ye | <u>a)</u> |
| Parts & Labor Warranty 1 Ye | 9) |
| , | g) |
| Electric Cooktop | ar |
| | |
| Heating Type Radia | nt |
| Surface Gla | ss |
| Element Type Glasste | эр |
| Number of Elements | 2 |
| controls D | ial |
| Countertop Cutout Height 3.0" (8 cr | n) |
| Countertop Cutout Width 20.0" (51 cr | n) |
| Countertop Cutout Depth 16.0" (41 cr | n) |
| Element #1 Size 5.5" (14 cr | n) |
| Element #1 Wattage 500 | .0 |
| Element #2 Size 7.0" (18 cr | n) |
| Element #2 Wattage 900 | |



