

TECHNICAL DATA SHEET

CW2024 Skifer

Vertical

USAGE: (SEE HAVWOODS QUICK REFERENCE GUIDE TO CHOOSING THE CORRECT FLOOR).



PRODUCT DETAILS

Product Code	CW2024	
Product Range	Vertical	
Construction	Solid	
Specie	Cork	
Pattern	Tile	
Process	Natural	
Finish	Natural	
Profile	PAR	
Edge Profile	Square Edge	
Top Layer	Cork	
Backing	N/A	
Thickness	25-35mm	
Width	900mm	
Length	600mm	
Pack Size	4.32m2	
Grade	Rustical	
Maintenance	Comprehensive maintenance instructions and materials are available from Havwoods for all floors.	

INSTALLATION METHODS

Fully Bonded	Yes* (recommended)
Nailed	No
Floated on underlay	No
Over Underfloor Heating	No

DESIGN CHARACTERISTICS

Patchwork cork tiles or panels produced by gluing and pressing several pieces of natural raw cork to be used as wallcoverings within buildings.

Standard dimensions are 900×600 and 600×300 mm and the thickness can vary from 25 to 35 mm depending on the type of texture. The surface can be natural or coloured.

N.B. The product grading criteria is inspected at each mill visually and should be taken as an approximation only. Please ask for further details

TECHNICAL CRITERIA

Origin	Europe
Responsible Certification	Please ask a member of staff for details
Janka Hardness Rating	1,200 lbf (5,340N)
Formaldehyde Emission	BDL (EN12149)
Pentachlorophenol Emission	NPD
Slip testing	Not assessed
Reaction to Fire Certification	Class E (EN13501-1)
Thermal Resistance	NPD

INSTALLATION AND WARRANTY All Havwoods floor must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Havwoods warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standards worldwide.

This technical data sheet was written by Havwoods International. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs use in the sheet are intended only as illustrations. No rights can be derived from them.



^{*} Subject to compatible subfloor and correct installation (see Installation Guidelines) including sensors

[#] Temperature of top-face must never be allowed to exceed 27°C. UFH protocol to control temperature conditions is recommended.