

# **TECHNICAL DATA SHEET**

## HW5606 Beech

## **Gold Leaf**

USAGE: (SEE HAVWOODS QUICK REFERENCE GUIDE TO CHOOSING THE CORRECT FLOOR).



### **PRODUCT DETAILS**

Product Code	HW5606	
Product Range	Gold Leaf	
Construction	Solid	
Specie	Beech	
Pattern	2-Strip	
Process	Sanded	
Finish	Matt Lacquered	
Profile	Tongue & Groove	
Edge Profile	Square Edge	
Top Layer	Beech	
Backing	N/A	
Thickness	22mm	
Width	130mm	
Length	2180mm (May include up to 25% shorter boards)	
Pack Size	1.70m²	
Grade	Select	
Maintenance	Comprehensive maintenance instructions and materials are available from Havwoods for all floors.	

### **INSTALLATION METHODS**

Fully Bonded	Yes* (recommended)
Nailed	Yes*
Floated on underlay	Yes (on clip system)
Over Underfloor Heating	No

#### **GRADING CRITERIA**

Known as either select or classic grade, typically this will have a mix of almost prime boards with other planks which have more knots. Slightly larger knots are allowed in this grade. Heartwood and colour variation in the timber should be expected and there may be some checks (cracks across the growth ring), sapwood and filler. The colour of the filler is selected to complement the wood rather than to match it exactly and it may vary from batch to batch.

N.B. The product grading criteria is inspected at each mill visually and should be taken as an approximation only. Please ask for further details

## **TECHNICAL CRITERIA**

Origin	Europe
Responsible Certification	PEFC <sup>™</sup> Certified (PEFC/16-37-1417)
Janka Hardness Rating	1,450 lbf (6,460N)
Formaldehyde Emission	E1 (EN 717-1)
Pentachlorophenol Emission	< 5ppm (CEN/TR 14823)
Slip testing	80 USRV
Reaction to Fire Certification	Cfl-s1 (EN 13501-1)
Thermal Conductivity	λ 0.16 W/m K

INSTALLATION AND WARRANTY All Havwoods floor must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Havwoods warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standards worldwide.





<sup>\*</sup> Subject to compatible subfloor and correct installation (see Installation Guidelines) including sensors.

<sup>\*\*</sup> This product may require on-site sanding prior to applying a suitable finish

<sup>#</sup> Temperature of top-face must never be allowed to exceed 27°C. UFH protocol to control temperature conditions is recommended