

# **TECHNICAL DATA SHEET**

## HW5608 Beech

### **Gold Leaf**

USAGE: (SEE HAVWOODS QUICK REFERENCE GUIDE TO CHOOSING THE CORRECT FLOOR).



#### **INSTALLATION METHODS**

Fully Bonded	Yes*
Nailed	Yes (on Batten System)
Floated on underlay	Yes (on Clip System)
Over Underfloor Heating	No

#### **GRADING CRITERIA**

Known as either select or classic grade, typically this will have a mix of almost prime boards with other planks which have more knots. Slightly larger knots are allowed in this grade. Heartwood and colour variation in the timber should be expected and there may be some checks (cracks across the growth ring), sapwood and filler. The colour of the filler is selected to complement the wood rather than to match it exactly and it may vary from batch to batch.

N.B. The product grading criteria is inspected at each mill visually and should be taken as an approximation only. Please ask for further details

#### **PRODUCT DETAILS**

Product Code	HW5608
Product Range	Gold Leaf
Construction	Solid
Specie	Beech
Pattern	2-Strip
Process	Leave unfinished
Finish	Unfinished
Profile	Tongue & Groove
Edge Profile	Square Edge
Top Layer	Beech
Backing	N/A
Thickness	22mm
Width	130mm
Length	2180mm (May include up to 25% shorter boards)
Pack Size	1.70m <sup>2</sup>
Grade	Select
Maintenance	Comprehensive maintenance instructions and materials are available from Havwoods for all floors.

#### **TECHNICAL CRITERIA**

Origin	Europe
<b>Responsible Certification</b>	PEFC <sup>™</sup> Certified (PEFC/16-37-1417)
Janka Hardness Rating	1,450 lbf (6,460N)
Formaldehyde Emission	E1
Pentachlorophenol Emission	< 5ppm
Slip testing	80 USRV
<b>Reaction to Fire Certification</b>	Cfl-s1 (EN 13501-1:2007)
Thermal Conductivity	λ 0.16 W/m K

\* Subject to compatible subfloor and correct installation (see Installation Guidelines) including sensors.

\*\* This product may require on-site sanding prior to applying a suitable finish

# Temperature of top-face must never be allowed to exceed 27°C. UFH protocol to control temperature conditions is rect ‡ Pack lengths will either 1950mm or 2400mm dependant upon stock availability.

necessary skills and take individual site circumstances into account. Havwoods warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standards worldwide.

This technical data sheet was written by Hawwoods International. At the time of writing and publiciation of the sheet, all inform is specified correctly. The company reserves the right to change the specifications of this product at any time without prior no to third parties. The photographs use in the sheet are intended only as illustrations. No rights can be derived from them.



Havwoods International, Carnforth Business Park, Oakwood Way, Carnforth, Lancashire LAS 9FD; Tel -+44 (0)1524 737 000; Fax - +44 (0)1524 737 001; info@havwoods.com www.havwoods.com