

# Technical Data Sheet

# HW5612 White Oak Gold Leaf

Usage: See Havwoods quick reference guide to choosing the correct floor



## Installation Methods

Fully Bonded	Yes* (recommended)
Nailed	Yes* (batten system)
Floated on underlay	Yes (clip floor system)
Over Underfloor Heating	Yes*# (Please ask for our technical guidelines)

## Grading Criteria

Known as either select or classic grade, typically this will have a mix of almost prime boards with other planks which have more knots. Slightly larger knots are allowed in this grade. Heartwood and colour variation in the timber should be expected and there may be some checks (cracks across the growth ring), sapwood and filler. The colour of the filler is intended to complement the natural structure of the wood, where features such as knots are in contrast to the surrounding timber, and it may vary from batch to batch.

**N.B.** The product grading criteria is inspected at each mill visually and should be taken as an approximation only. Please ask for further details

## Product Details

Product Code	HW5612
Product Range	Gold Leaf
Construction	Solid
Specie	European Oak (Quercus Robur)
Pattern	2-Strip
Process	Sanded
Finish	Matt Lacquered
Profile	Tongue & Groove
Edge Profile	Square Edge
Top Layer	European Oak (Quercus Robur)
Backing	N/A
Thickness	22mm
Width	130mm
Length	2180mm
Pack Size	1.7m <sup>2</sup>
Grade	Select
Maintenance	Comprehensive maintenance instructions and materials are available from Havwoods for all floors.

## Technical Criteria

Origin	Malaysia
Responsible Certification	PEFC™ Certified (PEFC/16-37-1417)
Janka Hardness Rating	1,120 lbf (4,980N)
Formaldehyde Emission	E1 (EN 717-1)
Pentachlorophenol Emission	< 5ppm (CEN/TR 14823)
Slip testing	80 USRV
Reaction to Fire Certification	Cfl-s1 (EN 13501-1)
Thermal Conductivity	λ 0.16 W/m K



<sup>^</sup> Please note that this is a smoked/fumed product. This reactive process will typically generate a wider range of colour variation in the product.

<sup>\*</sup> Subject to compatible subfloor and correct installation (see Installation Guidelines) including sensors.

<sup>\*\*</sup> This product may require on-site sanding prior to applying a suitable finish

<sup>#</sup> Temperature of top-face must never be allowed to exceed 27°C. UFH protocol to control temperature conditions is recommended.

<sup>‡</sup> Pack lengths will either 1950mm or 2400mm dependant upon stock availability.

**Installation and Warranty:** All Havwoods floor must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Havwoods warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standards worldwide.

This technical data sheet was written by Havwoods International. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs use in the sheet are intended only as illustrations. No rights can be derived from them.



Havwoods Limited, Carnforth Business Park, Oakwood Way,  
Carnforth, Lancashire LA5 9FD

Tel: +44 (0)1524 737 000; Fax: +44 (0)1524 737 001  
info@havwoods.com  
www.havwoods.com