

## **TECHNICAL DATA SHEET**

# **RECM3081 Dryden**

### Henley

USAGE: (SEE HAVWOODS QUICK REFERENCE GUIDE TO CHOOSING THE CORRECT FLOOR).



#### **PRODUCT DETAILS**

Product Code	RECM3081
<b>Product Range</b>	Henley
Construction	Engineered
Specie	European Oak
Pattern	1-Strip
Process	Fine Sawn & Worn
Finish	Oiled
Profile	Tongue & Groove
Edge Profile	Bevelled Edge
Top Layer	4mm European Oak
Backing	Eucalyptus/Birch Plywood
Thickness	15mm
Width	190mm
Length	1900mm (May include up to 25% shorter boards)
Pack Size	TBC
Grade	Rustic
Maintenance	Comprehensive maintenance instructions and materials are available from Havwoods for all floors.

#### **INSTALLATION METHODS**

Fully Bonded	Yes* (recommended)
Nailed	Yes*
Floated on underlay	No
Over Underfloor Heating	No

#### **GRADING CRITERIA**

Known as either natural or rustic grade this allows a virtually limitless size and number of knots. Heartwood will be used, there will be colour variation, sapwood and filler; you should expect checks (cracks across the growth ring) and possibly some end shake (cracks between the rings). The colour of the filler is selected to compliment the wood rather than to match it exactly and it may vary from batch to batch.

N.B. The product grading criteria is inspected at each mill visually and should be taken as an approximation only. Please ask for further details

#### **TECHNICAL CRITERIA**

Origin	China	
Responsible Certification	FSC® Certified (FSC-C009500)	
Janka Hardness Rating	1,120 lbf (4,980N)	
Formaldehyde Emission		
Pentachlorophenol Emission	< 5ppm (CEN/TR 14823)	
Slip testing		
Reaction to Fire Certification		
Thermal Conductivity		

INSTALLATION AND WARRANTY All Havwoods floor must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Havwoods warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standards worldwide.





<sup>\*</sup> Subject to compatible subfloor and correct installation (see Installation Guidelines) including sensors

<sup>\*\*</sup> This product may require on-site sanding prior to applying a suitable finish

<sup>#</sup> Temperature of top-face must never be allowed to exceed 27°C. UFH protocol to control temperature conditions is rec ‡ Pack lengths will vary between 1950mm or 2400mm dependant upon stock availability.