

TECHNICAL DATA SHEET

RECM4397 Chiselet

Design from Havwoods

USAGE: (SEE HAVWOODS QUICK REFERENCE GUIDE TO CHOOSING THE CORRECT FLOOR).



INSTALLATION METHODS

Fully Bonded	Yes* (recommended)
Nailed	No
Floated on underlay	No
Over Underfloor Heating	Yes*# (Please ask for our technical guidelines)

GRADING CRITERIA

Known as either natural or rustic grade this allows a virtually limitless size and number of knots. Heartwood will be used, there will be colour variation, sapwood and filler; you should expect checks (cracks across the growth ring) and possibly some end shake (cracks between the rings). The colour of the filler is selected to compliment the wood rather than to match it exactly and it may vary from batch to batch.

N.B. The product grading criteria is inspected at each mill visually and should be taken as an approximation only. Please ask for further details

PRODUCT DETAILS

Product CodeRECM4397Product RangeDesign from HavwoodsConstructionEngineeredSpecieEuropean OakPatternDesign PanelProcessFine AgedFinishStained & OiledProfileTongue & GrooveEdge ProfileSquare EdgeTop LayerSmm European OakBackingBirch PlywoodThickness20mmVidth800mmLength800mmPack Size0.64m²GradeRusticMaintenanceComprehensive maintenance instructions and materials are available from Havwoods for all floors.			
ConstructionEngineeredSpecieEuropean OakPatternDesign PanelProcessFine AgedFinishStained & OiledProfileTongue & GrooveEdge ProfileSquare EdgeTop LayerSmm European OakBackingBirch PlywoodThickness20mmWidth800mmLength800mmPack Size0.64m²GradeRusticMaintenanceComprehensive maintenance instructions and materials	Product Code	RECM4397	
Specie European Oak Pattern Design Panel Process Fine Aged Finish Stained & Oiled Profile Tongue & Groove Edge Profile Square Edge Top Layer Smm European Oak Backing Birch Plywood Thickness 20mm Width 800mm Length 800mm Pack Size 0.64m² Grade Rustic	Product Range	Design from Havwoods	
PatternDesign PanelProcessFine AgedFinishStained & OiledProfileTongue & GrooveEdge ProfileSquare EdgeTop LayerSmm European OakBackingBirch PlywoodThickness20mmWidth800mmLength800mmPack Size0.64m²GradeRusticMaintenanceComprehensive maintenance instructions and materials	Construction	Engineered	
Process Fine Aged Finish Stained & Oiled Profile Tongue & Groove Edge Profile Square Edge Top Layer Smm European Oak Backing Birch Plywood Thickness 20mm Width 800mm Length 800mm Grade Rustic Maintenance Comprehensive maintenance instructions and materials	Specie	European Oak	
Finish Stained & Oiled Profile Tongue & Groove Edge Profile Square Edge Top Layer Smm European Oak Backing Birch Plywood Thickness 20mm Width 800mm Length 800mm Grade Rustic Maintenance Comprehensive maintenance instructions and materials	Pattern	Design Panel	
Profile Tongue & Groove Edge Profile Square Edge Top Layer Smm European Oak Backing Birch Plywood Thickness 20mm Width 800mm Length 800mm Pack Size 0.64m² Grade Rustic Maintenance Comprehensive maintenance instructions and materials	Process	Fine Aged	
Edge Profile Square Edge Top Layer Smm European Oak Backing Birch Plywood Thickness 20mm Width 800mm Length 800mm Pack Size 0.64m² Grade Rustic Maintenance Comprehensive maintenance instructions and materials	Finish	Stained & Oiled	
Top Layer 5mm European Oak Backing Birch Plywood Thickness 20mm Width 800mm Length 800mm Pack Size 0.64m² Grade Rustic Maintenance Comprehensive maintenance instructions and materials	Profile	Tongue & Groove	
Backing Birch Plywood Thickness 20mm Width 800mm Length 800mm Pack Size 0.64m² Grade Rustic Maintenance Comprehensive maintenance instructions and materials	Edge Profile	Square Edge	
Thickness 20mm Width 800mm Length 800mm Pack Size 0.64m ² Grade Rustic Maintenance Comprehensive maintenance instructions and materials	Top Layer	5mm European Oak	
Width 800mm Length 800mm Pack Size 0.64m ² Grade Rustic Maintenance Comprehensive maintenance instructions and materials	Backing	Birch Plywood	
Length 800mm Pack Size 0.64m ² Grade Rustic Maintenance Comprehensive maintenance instructions and materials	Thickness	20mm	
Pack Size 0.64m ² Grade Rustic Maintenance Comprehensive maintenance instructions and materials	Width	800mm	
Grade Rustic Maintenance Comprehensive maintenance instructions and materials	Length	800mm	
Maintenance Comprehensive maintenance instructions and materials	Pack Size	0.64m²	
	Grade	Rustic	
	Maintenance	•	

TECHNICAL CRITERIA

Origin	Europe
Responsible Certification	Please ask a member of staff for details
Janka Hardness Rating	1,120 lbf (4,980N)
Formaldehyde Emission	E1(EN 717-1)
Pentachlorophenol Emission	< 5ppm (CEN/TR 14823)
Slip testing	95/48 PTV (CEN/TS 15676:2007)
Reaction to Fire Certification	Cfl-s1 (EN 13501-1:2007)
Thermal Conductivity	λ̃ 0.18 W/m K (EN 12664)

* Subject to compatible subfloor and correct installation (see Installation Guidelines) including sensors. ** This product may require on-site sanding prior to applying a suitable finish

Temperature of top-face must never be allowed to exceed 27°C. UFH protocol to control tem

rature conditions is reco

INSTALLATION AND WARRANTY All Havwoods floor must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Hawwoods warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standards worldwide.

This technical data sheet was written by Havwoods International. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs use in the sheet are intended only as illustrations. No rights can be derived from them.



Havwoods International, Carnforth Business Park, Oakwood Way, Carnforth, Lancashire LAS 9FD; Tel - +44 (0)1524 737 000; Fax - +44 (0)1524 737 001; info@havwoods.com www.havwoods.com