

TECHNICAL DATA SHEET

RECM4202 Darwin

Henley

USAGE: (SEE HAVWOODS QUICK REFERENCE GUIDE TO CHOOSING THE CORRECT FLOOR).



PRODUCT DETAILS

Product Code	RECM4202	
Product Range	Henley	
Construction	Engineered	
Specie	European Oak	
Pattern	1-Strip	
Process	Heavy Brushed	
Finish	Oiled	
Profile	Tongue & Groove	
Edge Profile	Bevelled Edge	
Top Layer	3mm European Oak	
Backing	Birch Plywood	
Thickness	14.5mm	
Width	180mm	
Length	1820mm	
Pack Size	1.96m²	
Grade	Rustic	
Maintenance	Comprehensive maintenance instructions and materials are available from Havwoods for all floors.	

INSTALLATION METHODS

Fully Bonded	Yes* (recommended)
Nailed	No
Floated on underlay	Yes*
Over Underfloor Heating	Yes*# wet-floor systems only

GRADING CRITERIA

Known as either natural or rustic grade this allows a virtually limitless size and number of knots. Heartwood will be used, there will be colour variation, sapwood and filler; you should expect checks (cracks across the growth ring) and possibly some end shake (cracks between the rings). The colour of the filler is carefully selected to compliment the wood rather than to match it exactly and it may vary from batch to batch.


N.B. The product grading criteria is inspected at each mill visually and should be taken as an approximation only. Please ask for further details

TECHNICAL CRITERIA

Origin	Europe
Responsible Certification	Please ask a member of staff for details
Janka Hardness Rating	1,120 lbf (4,980N)
Formaldehyde Emission	E1 (EN 717-1)
Pentachlorophenol Emission	Not detectable
Slip testing	NPD
Reaction to Fire Certification	Cfl-s1 (EN 13501-1:2007)
Thermal Conductivity	λ 0.15 W/m K (EN 12664)

INSTALLATION AND WARRANTY

All Havwoods floors must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Havwoods warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standards worldwide.







^{*} Subject to compatible subfloor and correct installation (see Installation Guidelines) including sensors.

[#]Temperature of top-face must never be allowed to exceed 27°C. UFH protocol to control temperature conditions is recommended