

TECHNICAL DATA SHEET

HW9082 V20

V Collection

USAGE: (SEE HAVWOODS QUICK REFERENCE GUIDE TO CHOOSING THE CORRECT FLOOR).



INSTALLATION METHODS

Fully Bonded	Yes* (recommended)
Nailed	Yes*
Floated on underlay	Yes*
Over Underfloor Heating	Yes*# (Water-fed systems only)

GRADING CRITERIA

Known as either natural or rustic grade this allows a virtually limitless size and number of knots. Heartwood will be used, there will be colour variation, sapwood and filler; you should expect checks (cracks across the growth ring) and possibly some end shake (cracks between the rings). The colour of the filler is carefully selected to compliment the wood rather than to match it exactly and it may vary from batch to batch.

N.B. The product grading criteria is inspected at each mill visually and should be taken as an approximation only. Please ask for further details

PRODUCT DETAILS

Product Code	HW9082
Product Range	V Collection
Construction	Engineered
Specie	European Oak
Pattern	1-Strip
Process	Sanded
Finish	UV Oiled
Profile	Tongue & Groove
Edge Profile	Bevelled Edge
Top Layer	5.5mm European Oak
Backing	Birch Plywood
Thickness	20mm
Width	180mm
Length	Random
Pack Size	ТВС
Grade	Rustic
Maintenance	Comprehensive maintenance instructions and materials are available from Havwoods for all floors.

TECHNICAL CRITERIA

Origin	Europe
Responsible Certification	Please ask a member of staff for details
Janka Hardness Rating	1,120 lbf (4,980N)
Formaldehyde Emission	E1 (EN 717-1:2004)
Pentachlorophenol Emission	< 5ppm (EN 17070:2006)
Slip testing	50/32 PTV (CEN/TS 15676:2007)
Reaction to Fire Certification	Cfl-s1 (EN 13501-1)
Thermal Conductivity	λ 0.16 W/mK (EN 12664)

* Subject to compatible subfloor and correct installation (see Installation Guidelines) including sensors. # Temperature of top-face must never be allowed to exceed 27*C. UFH protocol to control temperature conditions is recommended

INSTALLATION AND WARRANTY

All Havwoods floors must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Havwoods warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standards worldwide.

© This technical data sheet was written by Havwoods International. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this sheet are intended only as illustrations. No rights can be derived from them. 22-AUGUST-2003/FU Havwoods Limited, Carnforth Business Park, Oakwood Way, Carnforth LA5 9FD T. +44(0)1524 737000 F.+44(0)1524 737001 info@havwoods.co.uk www.havwoods.co.uk