

# **TECHNICAL DATA SHEET**

# HW673 Oak Villa

## **EuroPlank**

USAGE: (SEE HAVWOODS QUICK REFERENCE GUIDE TO CHOOSING THE CORRECT FLOOR).



## **PRODUCT DETAILS**

<b>Product Code</b>	HW673
Product Range	EuroPlank
Construction	Engineered
Specie	European Oak
Pattern	1-Strip
Process	Sanded
Finish	Satin Lacquered
Profile	Click System
Edge Profile	Square Edge
Top Layer	3mm Mongolian Oak
Backing	Eucalyptus/Poplar Plywood
Thickness	14.5mm
Width	140mm
Length	Random
Pack Size	2.03m²
Grade	Select
Maintenance	Comprehensive maintenance instructions and materials are available from Havwoods for all floors.

# INSTALLATION METHODS

Fully Bonded	Yes*
Nailed	No
Floated on underlay	Yes* (recommended)
Over Underfloor Heating	Yes*#

#### **GRADING CRITERIA**

Known as either select or classic grade, typically this will have a mix of almost prime boards with other planks which have more knots. Slightly larger knots are allowed in this grade. Heartwood and colour variation in the timber should be expected and there may be some checks (cracks across the growth ring), sapwood and filler. The colour of the filler is carefully selected to complement the wood rather than to match it exactly and it may vary from batch to batch.


N.B. The product grading criteria is inspected at each mill visually and should be taken as an approximation only. Please ask for further details

# **TECHNICAL CRITERIA**

Origin	Europe
Responsible Certification	Please ask a member of staff for details
Janka Hardness Rating	1,010 lbf (4,490N)
Formaldehyde Emission	E1
Pentachlorophenol Emission	Not detectable
Slip testing	55 PTV (CEN/TS 15676:2007)
Reaction to Fire Certification	Dfl-s1 (EN13501-1)
Thermal Conductivity	λ 0.15 W/m K

#### INSTALLATION AND WARRANTY

All Havwoods floors must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Havwoods warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standards worldwide.







<sup>\*</sup> Subject to compatible subfloor and correct installation (see Installation Guidelines) including sensors

<sup>#</sup>Temperature of top-face must never be allowed to exceed 27°C. UFH protocol to control temperature conditions is recommended