

TECHNICAL DATA SHEET

HW3966 Citadel

Venture Plank

USAGE: (SEE HAVWOODS QUICK REFERENCE GUIDE TO CHOOSING THE CORRECT FLOOR).



PRODUCT DETAILS

Product Code	HW3966
Product Range	Venture Plank
Construction	Engineered
Specie	European Oak
Pattern	1-Strip
Process	Brushed
Finish	Oiled
Profile	Tongue & Groove
Edge Profile	Bevelled Edge
Top Layer	4.5mm European Oak
Backing	Birch Plywood
Thickness	19mm (3/4")
Width	175mm (6 7/8")
Length	Random (Random)
Pack Size	1.30-1.73m2 (#VALUE!)
Grade	Classic
Maintenance	Comprehensive maintenance instructions and materials are available from Havwoods for all floors.

INSTALLATION METHODS

Glue Down	Yes* (recommended)
Nailed	No
Floated on underlay	Yes*
Over Underfloor Heating	Yes*# (please see our UFH guidelines)

GRADING CRITERIA

Known as either select or classic grade, typically this will have a mix of almost prime boards with other planks which have more knots. Slightly larger knots are allowed in this grade. Heartwood and colour variation in the timber should be expected and there may be some checks (cracks across the growth ring), sapwood and filler. The colour of the filler is carefully selected to complement the wood rather than to match it exactly and it may vary from batch to batch.

N.B. The product grading criteria is inspected at each mill visually and should be taken as an approximation only. Please ask for further details

TECHNICAL CRITERIA

Origin	Europe
Responsible Certification	Please ask a member of staff for details
Janka Hardness Rating	1,120 lbf (4,980N)
Formaldehyde Emission	BLQ ppm - TSCA VI Compliant
Slip testing	63/30 PTV (BS 7976-2:2002+A1:2013)
Critical Radiant Flux	Class I - ASTM E 648
Thermal Conductivity	λ 0.17 W/m K (EN 12664)





INSTALLATION AND WARRANTY

All Havwoods floors must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Havwoods warranty will apply only to floors which have been installed by a competent flooring installer comparable to NWFA standards or equivalent standards worldwide.

© This technical data sheet was written by Havwoods International. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this sheet are intended only as illustrations. No rights can be derived from them.

 $[\]hbox{* Subject to compatible subfloor and correct installation (see Installation Guidelines) including sensors}$

 $[\]ensuremath{^{**}}$ This product may require on-site sanding prior to applying a suitable finish

[#]Temperature of top-face must never be allowed to exceed 27°c/80°F. UFH protocol to control temperature conditions is recommended