



TECHNICAL DATA SHEET

HW966 ARENA WIDE PLANK

VENTURE PLANK

USAGE: SEE HAVWOODS QUICK REFERENCE GUIDE TO CHOOSING THE CORRECT FLOOR.



The photographs used in this sheet are intended only as illustrations, colours shown are only as accurate as the printing process or device screen will allow. Due to the size of this photograph, it does not provide any indication of grading. Please refer to our separate grading rules. No rights can be derived from them.

PRODUCT DETAILS

Product Code	HW966
Product Range	Venture Plank
Construction	Engineered
Species	European Oak
Pattern	1-Strip Pattern
Process	Sanded
Finish	UV Oiled
Profile	Tongue and Groove
Edge Profile	Micro-Bevelled Edge
Top Layer	6mm European Oak Lamella
Backing	Birch Plywood
Thickness	20mm
Width	260mm
Length	1950/2400mm (Packs contain split lengths, with up to 25% shorter boards. These may be half or 1/3 lengths)
Grade	Rustic
Maintenance	Comprehensive maintenance instructions and materials are available from Havwoods Ltd. for all floors. Contact your Havwoods consultant on 1300 428 966.

INSTALLATION METHODS

Fully Bonded	Yes* (Recommended)
Nailed	Yes*
Floated on underlay	Yes*
Over Underfloor Heating	Yes*# (to be installed over Wet Underfloor Heating Systems only. Please see UFH Installation Guidelines for details)

GRADING CRITERIA

Rustic grade, also known as natural grade, allows a virtually limitless size and number of knots. Heartwood will be used, there will be colour variation, sapwood and filler. You should expect checks (cracks across the growth ring) and possibly some end shake (cracks between the rings). The colour of the filler is carefully selected to compliment the wood rather than to match it exactly and it may vary from batch to batch.

NB: The product grading criteria is an approximation only. Please ask for details. Contact your Havwoods consultant on 1300 428 966.

TECHNICAL CRITERIA

Origin	Europe
Sustainability	Cradle to Cradle Certified™ BRONZE
Janka Hardness Rating	1,360 lbf (6,000N)
Formaldehyde Emission	E-1
Pentachlorophenol Emission	< 5ppm
Slip Testing	P3
European reaction to fire classification	Cfl-s1
Thermal Conductivity	0.17 W/mK

* Subject to compatible subfloor and correct installation (see Installation Guidelines) including sensors.

Temperature of top-face must never be allowed to exceed 27° C. Under Floor Heating (UFH) protocol to control temperature conditions is recommended.

INSTALLATION AND WARRANTY

All Havwoods floors must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Havwoods warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standard worldwide.

© This technical data sheet was written by Havwoods Limited, Carnforth Business Park, Oakwood Way, Carnforth Lancashire LA5 9FD. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this sheet are intended only as illustrations, colours shown are only as accurate as the printing process or device screen will allow. No rights can be derived from them.



HAVWOODS SYDNEY SHOWROOM
28 Margaret Street
Sydney CBD, NSW 2000

HAVWOODS MELBOURNE SHOWROOM
215 Roden Street
West Melbourne, VIC 3003

HAVWOODS NEWCASTLE SHOWROOM
150 King Street
Newcastle, NSW 2300

1300 428 966 | info@havwoods.com.au
www.havwoods.com.au