



TECHNICAL DATA SHEET

HW3812 JUBILEE

VENTURE PLANK

USAGE: SEE HAVWOODS QUICK REFERENCE GUIDE TO CHOOSING THE CORRECT FLOOR.



The photographs used in this sheet are intended only as illustrations, colours shown are only as accurate as the printing process or device screen will allow. Due to the size of this photograph, it does not provide any indication of grading. Please refer to our separate grading rules. No rights can be derived from them.

PRODUCT DETAILS

| | |
|---------------|---|
| Product Code | HW3812 |
| Product Range | Venture Plank |
| Construction | Engineered |
| Species | European Oak |
| Pattern | 1-Strip Pattern |
| Process | Heavy Brushed |
| Finish | White Natural Oiled Natural Oiled (Havwoods recommend a further coat of oil on all natural oiled products after installation) |
| Profile | Tongue and Groove |
| Edge Profile | Micro-Bevelled Edge |
| Top Layer | 6mm European Oak Lamella |
| Backing | Birch Plywood |
| Thickness | 20mm |
| Width | 180mm |
| Length | 1950/2400mm (Confirm length availability at time of order. Packs contain split lengths, with up to 25% shorter boards. These may be half or 1/3 lengths.) |
| Grade | Character |
| Maintenance | Comprehensive maintenance instructions and materials are available from Havwoods Ltd. for all floors. Contact your Havwoods consultant on 1300 428 966. |

INSTALLATION METHODS

| | |
|-------------------------|--|
| Fully Bonded | Yes* (Recommended) |
| Nailed | Yes* |
| Floated on underlay | Yes* |
| Over Underfloor Heating | Yes*# (to be installed over Wet Underfloor Heating Systems only. Please see UFH Installation Guidelines for details) |

GRADING CRITERIA

Character grade, also known as classic grade, typically will include both heartwood and sapwood and allows a wider range of colour variation. Knots are larger and you should expect checks (cracks across the growth ring). Filler will be used, the colour of which is carefully selected to complement the wood rather than to match it exactly. Colour of filler used may vary from batch to batch.

NB: The product grading criteria is an approximation only. Please ask for details. Contact your Havwoods consultant on 1300 428 966.

TECHNICAL CRITERIA

| | |
|--|------------------------------------|
| Origin | Europe |
| Sustainability | Cradle to Cradle Certified™ BRONZE |
| Janka Hardness Rating | 1,360 lbf (6,000N) |
| Formaldehyde Emission | E-1 |
| Pentachlorophenol Emission | < 5ppm |
| Slip Testing | P2 |
| European reaction to fire classification | Cfl-s1 |
| Thermal Conductivity | 0.17 W/mK |

* Subject to compatible subfloor and correct installation (see Installation Guidelines) including sensors.

Temperature of top-face must never be allowed to exceed 27 °C. Under Floor Heating (UFH) protocol to control temperature conditions is recommended.

INSTALLATION AND WARRANTY

All Havwoods floors must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Havwoods warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standard worldwide.

© This technical data sheet was written by Havwoods Limited, Carnforth Business Park, Oakwood Way, Carnforth Lancashire LA5 9FD. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this sheet are intended only as illustrations, colours shown are only as accurate as the printing process or device screen will allow. No rights can be derived from them.



HAVWOODS SYDNEY SHOWROOM
28 Margaret Street
Sydney CBD, NSW 2000

HAVWOODS MELBOURNE SHOWROOM
215 Roden Street
West Melbourne, VIC 3003

HAVWOODS NEWCASTLE SHOWROOM
150 King Street
Newcastle, NSW 2300

1300 428 966 | info@havwoods.com.au
www.havwoods.com.au