



TECHNICAL DATA SHEET

HO942 TREKKER ANTHRACITE WOOD GRAIN USAGE: COMMERCIAL AND RESIDENTIAL APPLICATIONS

(See Havwoods Quick Reference Guide to choosing the correct floor).



TREKKER ANTHRACITE WOOD GRAIN

PRODUCT DETAILS

| | |
|-------------------|--|
| Product Reference | HO942 |
| Width x Thickness | 157 x16mm |
| Board Type | Wood/Resin Composite |
| Pattern | 1-Strip Plank |
| Length | 3.2m |
| Composition | Wood Flour/Polymer |
| Maintenance | Comprehensive cleaning and maintenance instructions and materials are available from Havwoods Ltd. for all floors. |

INSTALLATION METHODS

| | |
|--------------------------|--|
| Fully Bonded | No |
| Fixing | Clips and screws are included (please ask a member of staff for details) |
| Floated on underlay | No |
| Over Under Floor Heating | No |

Origin: Europe

TECHNICAL CRITERIA

| Characteristics | Requirements –EN 15534-4 | Result |
|-------------------------------------|---|--|
| Humidity | Declaration | 3.10% |
| Cupping | Declaration | 0.05mm |
| Density | Declaration | 1449 Kg/m ³ |
| Slip Resistance | ≥ 36 | 60 PTV (Dry) 46 PTV (Wet) |
| Fire Resistance | | Bfl-s1 |
| Impact Resistance | ≤ 0.5mm | Max 0.10mm |
| Flexural Properties | F ¹ Max3300N (Mean) F ¹ Max3000N (Individual) Deflection under load (mean) Deflection under load (individual) | 1274N 1228N 1.6mm 1.7mm |
| Swelling and Water Absorption | Absorption (Mean) ≤ 4% (thickness) ≤ 0.8% (width) ≤ 0.4% (length) Absorption (Individual) ≤ 4% (thickness) ≤ 1.2% (width) ≤ 0.6% (length) Mean Absorption - 7% Individual Maximum - 7% | 3.00% 0.60% 0.20% 3.60% 0.70% 0.30% 3.90% 4.20% |
| Boiling Test | ≤ 7% (mean) | 3.70% |
| Composition | Declaration | 40%/60% Wood 40%/60% Polymer 10% Others |
| Vicat | Declaration | 85.2°C |
| HDT | Declaration | 74°C |
| Coef. Thermal expansion | ≤ 50 x 10-6K | 2.79 x 10-5mm/mm°C |
| Resistance to artificial weathering | Declaration | ΔL * 5 |
| Mark | Declaration | EN15534-4 P/C W 50 UC3 |

* Subject to compatible subfloor and correct installation (see Installation Guidelines) including sensors.

INSTALLATION AND WARRANTY

All Havwoods floors must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Havwoods warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standard worldwide.

© This technical data sheet was written by Havwoods Limited, Carnforth Business Park, Oakwood Way, Carnforth Lancashire LA5 9FD. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this sheet are intended only as illustrations. No rights can be derived from them.

