

TECHNICAL DATA SHEET

HO966 TREKKER ANTHRACITE FASCIA USAGE: COMMERCIAL AND RESIDENTIAL APPLICATIONS

(See Havwoods Quick Reference Guide to choosing the correct floor).



TREKKER ANTHRACITE FASCIA

PRODUCT DETAILS	
Product Reference	HO966
Width x Thickness	100 x 11mm
Board Type	Wood/Resin Composite
Pattern	1-Strip Plank
Length	1.5m
Composition	Wood Flour/Polymer
Maintenance	Comprehensive cleaning and maintenance instructions and materials are available from Havwoods Ltd. for all floors.

INSTALLATION METHODS


Fully Bonded	No			
Fixing	Clips and screws are included (please ask a member of staff for details)			
Floated on underlay	No			
Over Under Floor Heating	No			
Origin:	Europe			

TECHNICAL CRITERIA			
Characteristics	Requirements –EN 15534-4	Result	
Humidity	Declaration	3.10%	
Cupping	Declaration	0.05mm	
Density	Declaration	1449 Kg/m³	
Slip Resistance	≥ 36	60 PTV (Dry) 46 PTV (Wet)	
Impact Resistance	≤ 0.5mm	Max 0.10mm	
Flexural Properties	F¹ Max 3300N (Mean) F¹ Max 3000N (Individual) Deflection underload (mean) Deflection underload (individual)	1274N 1228N 1.6mm 1.7mm	
Swelling and Water Absorption	Absorption (Mean) ≤ 4% (thickness) ≤ 0.8% (width) ≤ 0.4% (length)	3.00% 0.60% 0.20%	
	Absorption (Individual) ≤ 4% (thickness) ≤ 1.2% (width) ≤ 0.6& (length) Mean Absorption-7% Individual Maximum-7%	3.60% 0.70% 0.20% 3.90% 4.20%	
Boiling Test	≤ 7% (mean)	3.70%	
Composition	Declaration	40%/60% Wood 40%/60% Polymer 10% Others	
Vicat	Declaration	85.2°C	
HDT	Declaration	74°C	
Coef. Thermal expansion	≤50 x 10-6K	2.79 x 10-5mm/mm°C	
Resistance to artificial weathering	Declaration	ΔL *5	
	Declaration	EN15534-4 P/C W 50 UC3	

^{*} Subject to compatible subfloor and correct installation (see Installation Guidelines) including sensors.

INSTALLATION AND WARRANTY

All Havwoods floors must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Havwoods warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standard worldwide.









esponsible forestry