

# **TECHNICAL DATA SHEET**

# **CW3204 Reyes White**

## **Vertical**

USAGE: (SEE HAVWOODS QUICK REFERENCE GUIDE TO CHOOSING THE CORRECT FLOOR).



### **PRODUCT DETAILS**

Product Code	CW3204	
Product Range	Vertical	
Construction	Solid	
Specie	Cork (Quercus Suber)	
Pattern	Tile	
Process	Natural	
Finish	Abrasion, Stain & Water Resistant	
Profile	PAR	
Edge Profile	Square Edge	
Top Layer	Cork (Quercus Suber)	
Backing	N/A (N/A)	
Thickness	30mm	
Width	150mm	
Length	150mm	
Pack Size	1.62m2	
Grade	3-D	
Maintenance	Comprehensive maintenance instructions and materials are available from Havwoods for all floors.	

#### **INSTALLATION METHODS**

Fully Bonded	Yes* (recommended)
Nailed	No
Floated on underlay	No
Over Underfloor Heating	No

### **GRADING CRITERIA**

Solid agglomerated cork tiles to be used as wallcoverings within buildings, contributing significantly to the acoustic and thermal performance of buildings, improving environmental comfort and reducing energy costs.

Tiles are shaped by CNC machining and finished with a waterbased protector for increased water and stain resistance.

N.B. The product grading criteria is inspected at each mill visually and should be taken as an approximation only. Please ask for further details

#### **TECHNICAL CRITERIA**

Origin	Europe
Responsible Certification	Please ask a member of staff for details
Janka Hardness Rating	1,200 lbf (5,340N)
Formaldehyde Emission	BDL (EN12149)
Pentachlorophenol Emission	NPD
Slip testing	Not assessed
Reaction to Fire Certification	Class E (EN13501-1)
Thermal Conductivity	NPD

INSTALLATION AND WARRANTY All Havwoods floor must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Havwoods warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standards worldwide.





<sup>\*</sup> Subject to compatible subfloor and correct installation (see Installation Guidelines) including sensors.

<sup>\*\*</sup> This product may require on-site sanding prior to applying a suitable finish

<sup>#</sup> Temperature of top-face must never be allowed to exceed 27°C. UFH protocol to control temperature conditions is recom ‡ Pack lengths will either 1950mm or 2400mm dependant upon stock availability.