

Technical Data Sheet



Usage: See Havwoods quick reference guide to choosing the correct floor

Installation Methods

Fully Bonded	Yes* (recommended)
Screwed	No

Grading Criteria

Known as either natural or rustic grade this allows a virtually limitless size and number of knots. Heartwood will be used, there will be colour variation, sapwood and filler; you should expect checks (cracks across the growth ring) and possibly some end shake (cracks between the rings). The colour of the filler is intended to complement the natural structure of the wood, where features such as knots are in contrast to the surrounding timber, and it may vary from batch to batch.

N.B. The product grading criteria is inspected at each mill visually and should be taken as an approximation only. Please ask for further details

Technical Criteria

Origin	Europe
Responsible Certification	Please ask a member of staff for details
Janka Hardness Rating	1,200 lbf (5,340N)
Formaldehyde Emission	BDL (EN12149)
Pentachlorophenol Emission	NPD
Reaction to Fire Certification	Class F (EN13501-1)
Thermal Conductivity	NPD

Fine Sanded Process

CW1004

Vertical

Cork (Quercus Suber)

Solid

Tile

Product Details

Product Code

Product Range

Construction Specie

Pattern

Finish	Waxed
Profile	PAR
Edge Profile	Square Edge
Top Layer	Cork (Quercus Suber)
Backing	
Thickness	3mm
Width	300mm
Length	600mm
Pack Size	15.84m2
Grade	Natural
Maintenance	Comprehensive maintenance instructions and materials are available from Havwoods for all floors.

* Please note that this is a smoked/fumed product. This reactive process will typically generate a wider range of colour variation in the product. * Subject to compatible subfloor and correct installation (see Installation Guidelines) including sensors.

** This product may require on-site sanding prior to applying a suitable finish

Temperature of top-face must never be allowed to exceed 27°C. UFH protocol to control temperature conditions is recommended. ‡ Pack lengths will either 1950mm or 2400mm dependant upon stock availability.

Installation and Warranty: All Havwoods floor must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Havwoods warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standards worldwide.

This technical data sheet was written by Hawwoods International. At the time of writing and publiciation of the si information is specified correctly. The company reserves the right to change the specifications of this product time without prior notice to third parties. The photographs use in the sheet are intended only as illustrations. No can be derived from them.



Havwoods Limited, Carnforth Business Park, Oakwood Way, Carnforth, Lancashire LA5 9FD

Tel: +44 (0)1524 737 000; Fax: +44 (0)1524 737 001 info@havwoods.com www.havwoods.com

Version 2