



The mark of

TECHNICAL DATA SHEET

HW1390 VERSAILLES NATURAL

VERSAILLES

USAGE: SEE HAVWOODS QUICK REFERENCE GUIDE TO CHOOSING THE CORRECT FLOOR.



INSTALLATION METHODS

Fully Bonded	Yes* (Recommended)
Nailed	Yes
Floated on underlay	No
Over Underfloor Heating	No

GRADING CRITERIA

Rustic grade, also known as natural grade, allows a virtually limitless size and number of knots. Heartwood will be used, there will be colour variation, sapwood and filler. You should expect checks (cracks across the growth ring) and possibly some end shake (cracks between the rings). The colour of the filler is carefully selected to compliment the wood rather than to match it exactly and it may vary from batch to batch.

NB: The product grading criteria is an approximation only. Please ask for details. Contact your Havwoods consultant on 1300 428 966.

PRODUCT DETAILS

Product Code	HW1390			
Product Range	Versailles			
Construction	Engineered			
Species	European Oal	<		
Pattern	Preassembled Versailles			
Process	Fine Aged			
Finish	Oiled			
Profile	Tongue and Groove			
Edge Profile	Micro-Bevelled Edge			
Top Layer	6mm European Oak Lamella			
Backing	Birch Plywood			
Thickness	20mm			
Width	800mm			
Length	800mm			
Pack Size	1.28m ²			
Grade	Rustic			
Maintenance	Comprehensive maintenance instructions and materials are available from Havwoods Ltd. for all floors. Contact your Havwoods consultant on 1300 328 966.			

TECHNICAL CRITERIA

Origin		China			
Sustainability		FSC® Certified			
Janka Hardness Rating		1,360 lbf (6,000N)			
Formaldehyde Emission		E1			
Pentachlorophenol Emission		< 5ppm			
Slip Testing		42/18 PTV			
European reaction to fire classification		Bfl-s1 (EN13501-1)			
Thermal Conductivity		0.16 W/m K			

INSTALLATION AND WARRANTY

All Havwoods floors must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Havwoods warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standard worldwide.

© This technical data sheet was written by Havwoods Limited, Carnforth Business Park, Oakwood Way, Carnforth Lancashire LA5 9FD. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this sheet are intended only as illustrations, colours shown are only as accurate as the printing process or device screen will allow. No rights can be derived from them.



HAVWOODS SYDNEY SHOWROOM

28 Margaret Street Sydney CBD, NSW 2000

HAVWOODS MELBOURNE SHOWROOM

215 Roden Street West Melbourne, VIC 3003

1300 428 966 | info@havwoods.com.au www.havwoods.com.au

^{*} Subject to compatible subfloor and correct installation (see Installation Guidelines) including sensors

[#] Temperature of top-face must never be allowed to exceed 27 °C. Under Floor Heating (UFH) protocol to control temperature conditions is recommended.