



TECHNICAL DATA SHEET

HW673 OAK VILLA

EUROPLANK

USAGE: SEE HAVWOODS QUICK REFERENCE GUIDE TO CHOOSING THE CORRECT FLOOR.



The photographs used in this sheet are intended only as illustrations, colours shown are only as accurate as the printing process or device screen will allow. Due to the size of this photograph, it does not provide any indication of grading. Please refer to our separate grading rules. No rights can be derived from them.

PRODUCT DETAILS

Product Code	HW673
Product Range	Europlank
Construction	Engineered
Species	European Oak
Pattern	1-Strip Pattern
Process	Sanded
Finish	Satin Lacquered
Profile	Click System
Edge Profile	Square Edge
Top Layer	3mm European Oak
Backing	Eucalyptus
Thickness	14.5mm
Width	140mm
Length	1820mm (Packs contain split lengths, with up to 25% shorter boards. These may be half or 1/3 lengths)
Grade	Select
Maintenance	Comprehensive maintenance instructions and materials are available from Havwoods Ltd. for all floors. Contact your Havwoods consultant on 1300 428 966.

INSTALLATION METHODS

Fully Bonded	Yes*
Nailed	No
Floated on underlay	Yes* (Recommended)
Over Underfloor Heating	Yes*#

GRADING CRITERIA

Select grade typically this will have a mix of almost prime boards, with other planks which have more knots. Slightly larger knots are allowed in this grade. Heartwood and colour variation in the timber should be expected and there may be some checks (cracks across the growth ring), sapwood and filler. The colour of the filler is carefully selected to compliment the wood rather than to match it exactly and it may vary from batch to batch.

NB: The product grading criteria is an approximation only. Please ask for details. Contact your Havwoods consultant on 1300 428 966.

TECHNICAL CRITERIA

Origin	China
Janka Hardness Rating	1,010 lbf (4,490N)
Formaldehyde Emission	E-1
Pentachlorophenol Emission	Not detectable
Slip Testing	P2
European reaction to fire classification	Dfl-s1
Thermal Conductivity	0.15 W/mK

HAVWOODS SYDNEY SHOWROOM

28 Margaret Street
Sydney CBD, NSW 2000



HAVWOODS MELBOURNE SHOWROOM

215 Roden Street
West Melbourne, VIC 3003

HAVWOODS NEWCASTLE SHOWROOM

150 King Street
Newcastle, NSW 2300



1300 428 966 | info@havwoods.com.au

www.havwoods.com.au

* Subject to compatible subfloor and correct installation (see Installation Guidelines) including sensors.

Temperature of top-face must never be allowed to exceed 27°C. Under Floor Heating (UFH) protocol to control temperature conditions is recommended.

INSTALLATION AND WARRANTY

All Havwoods floors must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Havwoods warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standard worldwide.

© This technical data sheet was written by Havwoods Limited, Carnforth Business Park, Oakwood Way, Carnforth Lancashire LA5 9FD. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this sheet are intended only as illustrations, colours shown are only as accurate as the printing process or device screen will allow. No rights can be derived from them.