

cradietocradie BRONZE

TECHNICAL DATA SHEET

HW3003 ARENA HERRINGBONE

VENTURE PLANK

USAGE: SEE HAVWOODS QUICK REFERENCE GUIDE TO CHOOSING THE CORRECT FLOOR.



The photographs used in this sheet are intended only as illustrations, colours shown are only as accurate as the printing process or device screen will allow. Due to the size of this photograph, it does not provide any indication of grading. Please refer to our separate grading rules. No rights can be derived from them.

PRODUCT DETAILS

Product Code	HW3003	
Product Range	Venture Plank	
Construction	Engineered	
Species	European Oak	
Pattern	Herringbone	
Process	Sanded	
Finish	UV Oiled	
Profile	Tongue and Groove	
Edge Profile	Micro-Bevelled Edge	
Top Layer	4mm European Oak Lamella	
Backing	Birch Plywood	
Thickness	13mm	
Width	120mm	
Length	600mm	
Grade	Prime	
Maintenance	Comprehensive maintenance instructions and materials are available from Havwoods for all floors. Contact your Havwoods consultant on 1300 428 966.	

INSTALLATION METHODS

Fully Bonded	Yes* (Recommended)
Nailed	No
Floated on underlay	No
Over Underfloor Heating	Yes*

GRADING CRITERIA

Typically, prime grade has few, if any knots, and these will be of minimal size. There will also be a minimal amount of sapwood defects and filler, if any at all. Where filler is used its colour is carefully selected to complement the wood rather than to match it exactly, and the colour of the filler may vary from batch to batch. There will be a relatively small amount of colour variation in the timber itself.

NB: The product grading criteria is an approximation only. Please ask for details. Contact your Havwoods consultant on 1300 428 966.

TECHNICAL CRITERIA

Origin	Europe
Sustainability	Cradle to Cradle Certified™ BRONZE
Janka Hardness Rating	1,360 lbf (6,000N)
Formaldehyde Emission	E-1
Pentachlorophenol Emission	< 5ppm
Slip Testing	P3
European reaction to fire classification	Cfl-s1
Thermal Conductivity	0.17 W/mK

* Subject to compatible subfloor and correct installation (see Installation Guidelines) including sensors

INSTALLATION AND WARRANTY

All Havwoods floors must be installed by a qualified installer who will have the necessary skills and take individual site circumstances into account. Havwoods warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standard worldwide.

© This technical data sheet was written by Havwoods Limited, Carnforth Business Park, Oakwood Way, Carnforth Lancashire LA5 9FD. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this sheet are intended only as illustrations, colours shown are only as accurate as the printing process or device screen will allow. No rights can be derived from them.







28 Margaret Street Sydney CBD, NSW 2000

HAVWOODS MELBOURNE SHOWROOM

215 Roden Street West Melbourne, VIC 3003

HAVWOODS NEWCASTLE SHOWROOM

150 King Street Newcaslte, NSW 2300

1300 428 966 | info@havwoods.com.au www.havwoods.com.au

[#] Temperature of top-face must never be allowed to exceed 27°C. Under Floor Heating (UFH) protocol to control temperature conditions is recommended.