

# **TECHNICAL DATA SHEET**

# HRC2036 Gully

## Vertical

USAGE: (SEE HAVWOODS QUICK REFERENCE GUIDE TO CHOOSING THE CORRECT FLOOR).



## INSTALLATION METHODS

Glue Down	Yes* (recommended)
Nailed	No
Floated on underlay	Yes*
Over Underfloor Heating	No

# **GRADING CRITERIA**

Known as either natural or rustic grade this allows a virtually limitless size and number of knots. Heartwood will be used, there will be colour variation, sapwood and filler; you should expect checks (cracks across the growth ring) and possibly some end shake (cracks between the rings). The colour of the filler is selected to compliment the wood rather than to match it exactly and it may vary from batch to batch.

#### The above image is a finished product and should only be used as a design match

#### **PRODUCT DETAILS**

Product Code	HRC2036
Product Range	Vertical
Construction	Solid
Specie	Fir
Pattern	1-Strip
Process	Original Surface
Finish	Unfinished
Profile	PAR
Edge Profile	Reclaimed Edge
Top Layer	Fir
Backing	N/A
Thickness	4mm (1/8")
Width	50-150mm (2" - 5 7/8")
Length	300-1500mm (11 3/4" - 59")
Pack Size	TBC (TBC)
Grade	Rustic
Maintenance	Comprehensive maintenance instructions and materials are available from Havwoods for all floors.

### N.B. The product grading criteria is inspected at each mill visually and should be taken as an approximation only. Please ask for further details

# **TECHNICAL CRITERIA**

Origin	China
Responsible Certification	Please ask a member of staff for details
Janka Hardness Rating	700 lbf (3,110N)
Formaldehyde Emission	
Slip testing	Not assessed
Critical Radiant Flux	
Thermal Conductivity	NPD



\* Subject to compatible subfloor and correct installation (see Installation Guidelines) including sensors

\*\* This product may require on-site sanding prior to applying a suitable finish

# Temperature of top-face must never be allowed to exceed 27°c/80°F. UFH protocol to control temperature conditions is recommended.

 $\ddagger$  Pack lengths will vary between 1950mm or 2400mm dependant upon stock availability.

### INSTALLATION AND WARRANTY

All Havwoods floors must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Havwoods warranty will apply only to floors which have been installed by a competent flooring installer comparable to NWFA standards or equivalent standards worldwide.

© This technical data sheet was written by Havwoods International. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this sheet are intended only as illustrations. No rights can be derived from them.

Havwoods International (North America); 151 W 18th St, New York, NY 1011, USA Tel: 1 844 808 9663 (WOOD) Info@havwoodsusa.com