

# **TECHNICAL DATA SHEET**

# CW2024 Skifer

### Vertical

USAGE: (SEE HAVWOODS QUICK REFERENCE GUIDE TO CHOOSING THE CORRECT FLOOR).



### **PRODUCT DETAILS**

Product Code	CW2024
Product Range	Vertical
Construction	Solid
Specie	Cork
Pattern	Tile
Process	Natural
Finish	Natural
Profile	PAR
Edge Profile	Square Edge
Top Layer	Cork
Backing	N/A
Thickness	25-35mm (1" - 1 3/8")
Width	900mm (35 3/8")
Length	600mm (23 5/8")
Pack Size	4.32m2 (46.50ft²)
Grade	Rustical
Maintenance	Comprehensive maintenance instructions and materials are available from Havwoods for all floors.

## **INSTALLATION METHODS**

Fully Bonded	Yes* (recommended)
Nailed	No
Floated on underlay	No
Over Underfloor Heating	No

#### **DESIGN CHARACTERISTICS**

Patchwork cork tiles or panels produced by gluing and pressing several pieces of natural raw cork to be used as wallcoverings within buildings.

Standard dimensions are  $900 \times 600$  and  $600 \times 300$  mm and the thickness can vary from 25 to 35 mm depending on the type of texture. The surface can be natural or coloured.

N.B. The product grading criteria is inspected at each mill visually and should be taken as an approximation only. Please ask for further details

### **TECHNICAL CRITERIA**

Origin	Europe
Responsible Certification	Please ask a member of staff for details
Janka Hardness Rating	1,200 lbf (5,340N)
Formaldehyde Emission	BDL (EN12149)
Slip testing	Not assessed
Critical Radiant Flux	Class E (EN13501-1)
Thermal Conductivity	NPD



**INSTALLATION AND WARRANTY** All Havwoods floor must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Havwoods warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standards worldwide.

This technical data sheet was written by Havwoods International. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs use in the sheet are intended only as illustrations. No rights can be derived from them.

<sup>\*</sup> Subject to compatible subfloor and correct installation (see Installation Guidelines) including sensors.

<sup>#</sup> Temperature of top-face must never be allowed to exceed 27°C. UFH protocol to control temperature conditions is recommended.