



## TECHNICAL DATA SHEET

### CW3106 Modo White

#### Vertical

USAGE: (SEE HAVWOODS QUICK REFERENCE GUIDE TO CHOOSING THE CORRECT FLOOR).



#### PRODUCT DETAILS

<b>Product Code</b>	CW3106
<b>Product Range</b>	Vertical
<b>Construction</b>	Solid
<b>Specie</b>	Cork
<b>Pattern</b>	Tile
<b>Process</b>	Natural
<b>Finish</b>	Abrasion, Stain & Water Resistant
<b>Profile</b>	PAR
<b>Edge Profile</b>	Square Edge
<b>Top Layer</b>	Cork
<b>Backing</b>	N/A
<b>Thickness</b>	30mm (1 1/8")
<b>Width</b>	300mm (11 3/4")
<b>Length</b>	300mm (11 3/4")
<b>Pack Size</b>	1.62m <sup>2</sup> (17.44ft <sup>2</sup> )
<b>Grade</b>	3-D
<b>Maintenance</b>	Comprehensive maintenance instructions and materials are available from Havwoods for all floors.

#### INSTALLATION METHODS

<b>Fully Bonded</b>	Yes* (recommended)
<b>Nailed</b>	No
<b>Floated on underlay</b>	No
<b>Over Underfloor Heating</b>	No

#### DESIGN CHARACTERISTICS

Solid agglomerated cork tiles to be used as wallcoverings within buildings, contributing significantly to the acoustic and thermal performance of buildings, improving environmental comfort and reducing energy costs. Tiles are shaped by CNC machining and finished with a waterbased protector for increased water and stain resistance.

N.B. The product grading criteria is inspected at each mill visually and should be taken as an approximation only. Please ask for further details

#### TECHNICAL CRITERIA

<b>Origin</b>	Europe
<b>Responsible Certification</b>	Please ask a member of staff for details
<b>Janka Hardness Rating</b>	1,200 lbf (5,340N)
<b>Formaldehyde Emission</b>	BDL (EN12149)
<b>Slip testing</b>	Not assessed
<b>Critical Radiant Flux</b>	Class E (EN13501-1)
<b>Thermal Conductivity</b>	NPD



\* Subject to compatible subfloor and correct installation (see Installation Guidelines) including sensors.

# Temperature of top-face must never be allowed to exceed 27°C. UFH protocol to control temperature conditions is recommended.

**INSTALLATION AND WARRANTY** All Havwoods floor must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Havwoods warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standards worldwide.

This technical data sheet was written by Havwoods International. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs use in the sheet are intended only as illustrations. No rights can be derived from them.

20-DECEMBER-2019/EU

Havwoods International (North America);  
151 W 18th St, New York, NY 1011, USA  
Tel: 1 844 808 9663 (WOOD)  
com www.havwoodsusa.com

info@havwoodsusa.