

TECHNICAL DATA SHEET

HW16409C COLUMBA PLANK

THE ITALIAN COLLECTION

USAGE: SEE HAVWOODS QUICK REFERENCE GUIDE TO CHOOSING THE CORRECT FLOOR.



The photographs used in this sheet are intended only as illustrations, colours shown are only as accurate as the printing process or device screen will allow. Due to the size of this photograph, it does not provide any indication of grading. Please refer to our separate grading rules. No rights can be derived from them.

PRODUCT DETAILS

Product Code	HW16409C		
Product Range	The Italian Co	llection	
Construction	Engineered		
Species	European Oak	<	
Pattern	1-Strip Patterr	1	
Process	Brushed		
Finish	UV Oiled		
Profile	Tongue and G	iroove	
Edge Profile	Micro-bevelle	d Edge	
Top Layer	3.7mm Europe	ean Oak L	amella
Backing	Birch Plywood	t	
Thickness	10mm		
Width	120mm		
Length			may contain split lengths, with up These may be half or 1/3 lengths)
Grade	Character		
Maintenance	Comprehensive maintenance instructions and materials are available from Havwoods Ltd. for all floors. Contact your Havwoods consultant on 1300 428 966.		
Warranty: Commercial	N/A		
Warranty: Residential	20 Year Structural Integrity Warranty		

INSTALLATION METHODS

Fully Bonded	Yes* (Recommended)
Nailed	No
Floated on underlay	No
Over Underfloor Heating	Yes*# (to be installed over Wet Underfloor Heating Systems only. Please see UFH Installation Guidelines for details)

GRADING CRITERIA

Character grade, also known as classic grade, typically will include both heartwood and sapwood and allows a wider range of colour variation. Knots are larger and you should expect checks (cracks across the growth ring). Filler will be used, the colour of which is carefully selected to complement the wood rather than to match it exactly. Colour of filler used may vary from batch to batch.

NB: The product grading criteria is an approximation only. Please ask for details. Contact your Havwoods consultant on 1300 428 966.

TECHNICAL CRITERIA

Origin	Europe	
Responsibly Sourced	FSC* Certified (FSC-C009500)	
Janka Hardness Rating	1,120 lbf (4,980N)	
Formaldehyde Emission	E1 (EN 717-1;2006)	
Pentachlorophenol Emission	< 5ppm (CEN/TR 14823)	
Slip Testing	P2	
Reaction to Fire Certification	Cfl-s1 (EN 13501-1)	
Thermal Conductivity	λ 0.19 W/m K (EN 12664)	

More information about FSC* certified products can be found here: https://au.fsc.org/en-au.fsc.org



The mark of responsible forestry

INSTALLATION AND WARRANTY

All Havwoods floors must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Havwoods warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standard worldwide and maintained according to our Care and Maintenance instructions.

© This technical data sheet was written by Havwoods Limited, Carnforth Business Park, Oakwood Way, Carnforth Lancashire LA5 9FD. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this sheet are intended only as illustrations, colours shown are only as accurate as the printing process or device screen will allow. No rights can be derived from them.





HAVWOODS SYDNEY SHOWROOM

28 Margaret Street Sydney CBD, NSW 2000

HAVWOODS MELBOURNE SHOWROOM

215 Roden Street West Melbourne, VIC 3003

HAVWOODS NEWCASTLE SHOWROOM

150 King Street Newcaslte, NSW 2300

1300 428 966 | info@havwoods.com.au www.havwoods.com.au

^{*} Subject to compatible subfloor and correct installation (see Installation Guidelines) including sensors.

[#] Temperature of top-face must never be allowed to exceed 27 °C. Under Floor Heating (UFH) protocol to control temperature conditions is recommended.