

TECHNICAL DATA SHEET

HW1090 European Oak

Gold Leaf

USAGE: (SEE HAVWOODS QUICK REFERENCE GUIDE TO CHOOSING THE CORRECT FLOOR).



PRODUCT DETAILS

Product Code	HW1090	
Product Range	Gold Leaf	
Construction	Solid	
Specie	European Oak(Quercus Robur)	
Pattern	Herringbone	
Process	Sanding Required**	
Finish	Unfinished	
Profile	Tongue & Groove	
Edge Profile	Square Edge	
Top Layer	European Oak(Quercus Robur)	
Backing	N/A(N/A)	
Backing Thickness	N/A(N/A) 22mm	
Thickness	22mm	
Thickness Width	22mm 70mm	
Thickness Width Length	22mm 70mm 230mm	

INSTALLATION METHODS

Fully Bonded	Yes* (recommended)
Nailed	No
Floated on underlay	No
Over Underfloor Heating	No

GRADING CRITERIA

Typically, prime grade has few, if any knots, and these will be of minimal size. There will also be a minimal amount of sapwood and filler, if any at all. Where filler is used its colour is selected to complement the wood rather than to match it exactly and the colour of the filler may vary from batch to batch. There will be a relatively small amount of colour variation in the timber itself.

N.B. The product grading criteria is inspected at each mill visually and should be taken as an approximation only. Please ask for further details

TECHNICAL CRITERIA

Origin	United Kingdom
Responsible Certification	Please ask a member of staff for details
Janka Hardness Rating	1,120 lbf (4,980N)
Formaldehyde Emission	E1 (EN 717-1)
Pentachlorophenol Emission	< 5ppm (CEN/TR 14823)
Slip testing	Not assessed as unfinished
Reaction to Fire Certification	Cfl-s1 (EN 13501-1:2007)
Thermal Conductivity	λ 0.11 W/m K (EN 12664)

INSTALLATION AND WARRANTY All Havwoods floor must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Havwoods warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standards worldwide.





^{**} This product may require on-site sanding prior to applying a suitable finish

[#] Temperature of top-face must never be allowed to exceed 27°C. UFH protocol to control temperature conditions is recon ‡ Pack lengths will either 1950mm or 2400mm dependant upon stock availability.