

# **TECHNICAL DATA SHEET**

# **HW1134 Eston**

## **Venture Plank**

USAGE: (SEE HAVWOODS QUICK REFERENCE GUIDE TO CHOOSING THE CORRECT FLOOR).



## **PRODUCT DETAILS**

Product Code	HW1134	
Product Range	Venture Plank	
Construction	Engineered	
Specie	European Oak (Quercus Robur)	
Pattern	Versailles	
Process	Brushed	
Finish	UV Oiled	
Profile	Tongue & Groove	
Edge Profile	Bevelled Edge	
Top Layer	6mm European Oak (Quercus Robur)	
Backing	Birch Plywood (Betula spp.)	
Thickness	20mm	
	2011111	
Width	840mm	
Width Length		
	840mm	
Length	840mm 840mm	

#### **INSTALLATION METHODS**

Fully Bonded	Yes* (recommended)
Nailed	Yes*
Floated on underlay	No
Over Underfloor Heating	Yes*# (Please ask for our technical guidelines)

## **GRADING CRITERIA**

Typically, character grade will include both heartwood and sapwood and allows a wider range of colour variation. Knots are larger and you should expect checks (cracks across the growth ring). Filler will be use, the colour of which is selected to complement the wood rather than to match it exactly, and it may vary from batch to batch.

N.B. The product grading criteria is inspected at each mill visually and should be taken as an approximation only. Please ask for further details

#### **TECHNICAL CRITERIA**

Origin	Russia
Responsible Certification	Please ask a member of staff for details
Janka Hardness Rating	1,120 lbf (4,980N)
Formaldehyde Emission	E1(EN 717-1)
Pentachlorophenol Emission	< 5ppm (CEN/TR 14823)
Slip testing	71/29 PTV (CEN/TS 15676:2007)
Reaction to Fire Certification	Cfl-s1 (EN 13501-1:2007)
Thermal Conductivity	λ 0.17 W/m K (EN 12664)

INSTALLATION AND WARRANTY All Havwoods floor must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Havwoods warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standards worldwide.





<sup>\*</sup> Subject to compatible subfloor and correct installation (see Installation Guidelines) including sensors.

<sup>\*\*</sup> This product may require on-site sanding prior to applying a suitable finish

<sup>#</sup> Temperature of top-face must never be allowed to exceed 27°C. UFH protocol to control temperature conditions is recom ‡ Pack lengths will either 1950mm or 2400mm dependant upon stock availability.