


TECHNICAL DATA SHEET

HW3288 Tortona

Venture Plank

USAGE: (SEE HAVWOODS QUICK REFERENCE GUIDE TO CHOOSING THE CORRECT FLOOR).



INSTALLATION METHODS

Fully Bonded	Yes* (recommended)
Nailed	No
Floated on underlay	No
Over Underfloor Heating	Yes*# (Please ask for our technical guidelines)

GRADING CRITERIA

Typically, character grade will include both heartwood and sapwood and allows a wider range of colour variation. Knots are larger and you should expect checks (cracks across the growth ring). Filler will be use, the colour of which is selected to complement the wood rather than to match it exactly, and it may vary from batch to batch.

N.B. The product grading criteria is inspected at each mill visually and should be taken as an approximation only. Please ask for further details

PRODUCT DETAILS

Product Code	HW3288	
Product Range	Venture Plank	
Construction	Engineered	
Specie	European Oak (Quercus Robur)	
Pattern	Herringbone	
Process	Sanded	
Finish	UV Oiled	
Profile	Tongue & Groove	
Edge Profile	4-Sided Bevelled Edge	
Top Layer	6mm European Oak (Quercus Robur)	
Backing	Birch Plywood (Betula spp.)	
Thickness	20mm	
Width	130mm	
Length	650mm	
Pack Size	0.34m²	
Grade	Character	
Maintenance	Comprehensive maintenance instructions and materials are available from Havwoods for all floors.	

TECHNICAL CRITERIA

Origin	Europe	
Responsible Certification	Please ask a member of staff for details	
Janka Hardness Rating	1,120 lbf (4,980N)	
Formaldehyde Emission	E1(EN 717-1)	
Pentachlorophenol Emission	< 5ppm (CEN/TR 14823)	
Slip testing	65/35 PTV (CEN/TS 15676:2007)	
Reaction to Fire Certification	Cfl-s1 (EN 13501-1:2007)	
Thermal Conductivity	λ̃ 0.10 W/m K (EN 12664)	

* Subject to compatible subfloor and correct installation (see Installation Guidelines) including sensors.

** This product may require on-site sanding prior to applying a suitable finish

Temperature of top-face must never be allowed to exceed 27°C. UFH protocol to control temperature conditions is recom ‡ Pack lengths will either 1950mm or 2400mm dependant upon stock availability.

INSTALLATION AND WARRANTY All Havwoods floor must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Hawwoods warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standards worldwide.

This technical data sheet was written by Hawwoods International. At the time of writing and publiciation of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs use in the sheet are intended only as illustrations. No rights can be derived from them.



Havwoods International, Carnforth Business Park, Oakwood Way, Carnforth, Lancashire LAS 9FD; Tel - +44 (0)1524 737 000; Fax - +44 (0)1524 737 001; info@havwoods.com www.havwoods.com