

# **TECHNICAL DATA SHEET**

## **HRC1905 Notus**

## **Vertical**

USAGE: (SEE HAVWOODS QUICK REFERENCE GUIDE TO CHOOSING THE CORRECT FLOOR).



## **PRODUCT DETAILS**

Product Code	HRC1905	
<b>Product Range</b>	Vertical	
Construction	Solid	
Specie	American Pine (Hemlock/Pine)	
Pattern	1-Strip	
Process	Weathered	
Finish	Unfinished	
Profile	PAR	
Edge Profile	Reclaimed Edge	
Top Layer	Pine (Hemlock/Pine)	
Backing	N/A (N/A)	
Thickness	19mm	
Width	115-290mm	
Length	Random	
Pack Size	TBC	
Grade	Rustic	
Maintenance	Comprehensive maintenance instructions and materials are available from Havwoods for all floors.	

### **INSTALLATION METHODS**

Fully Bonded	Yes* (recommended)
Nailed	Yes*
Floated on underlay	No
Over Underfloor Heating	No

### **GRADING CRITERIA**

Known as either natural or rustic grade this allows a virtually limitless size and number of knots. Heartwood will be used, there will be colour variation, sapwood and filler; you should expect checks (cracks across the growth ring) and possibly some end shake (cracks between the rings). The colour of the filler is selected to compliment the wood rather than to match it exactly and it may vary from batch to batch.

N.B. The product grading criteria is inspected at each mill visually and should be taken as an approximation only. Please ask for further details

### **TECHNICAL CRITERIA**

Origin	USA
Responsible Certification	FSC® Certified (FSC-C009500)
Janka Hardness Rating	540 lbf (2,420N)
Formaldehyde Emission	E1 (EN 717-1)
Pentachlorophenol Emission	< 5ppm (CEN/TR 14823)
Slip testing	Not assessed
Reaction to Fire Certification	Class D (EU) / Class 4 (UK)
Thermal Conductivity	NPD

INSTALLATION AND WARRANTY All Havwoods floor must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Havwoods warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standards worldwide.





<sup>\*</sup> Subject to compatible subfloor and correct installation (see Installation Guidelines) including sensors.

<sup>\*\*</sup> This product may require on-site sanding prior to applying a suitable finish

<sup>#</sup> Temperature of top-face must never be allowed to exceed 27°C. UFH protocol to control temperature conditions is record;

‡ Pack lengths will either 1950mm or 2400mm dependant upon stock availability.