

TECHNICAL DATA SHEET

HRC4002 Cove

Vertical

USAGE: (SEE HAVWOODS QUICK REFERENCE GUIDE TO CHOOSING THE CORRECT FLOOR).



PRODUCT DETAILS

Product Range Vertical Construction Solid Specie European Oak (Oak) Pattern 1-Strip Process Hand Textured Finish Oiled Profile PAR Edge Profile Square Edge Top Layer European Oak (Oak) Backing N/A (N/A) Thickness 4mm Width 100mm Length 300-1200mm Pack Size Grade Rustic		
Construction Solid Specie European Oak (Oak) Pattern 1-Strip Process Hand Textured Finish Oiled Profile PAR Edge Profile Square Edge Top Layer European Oak (Oak) Backing N/A (N/A) Thickness 4mm Width 100mm Length 300-1200mm Pack Size Grade Rustic Maintenance Comprehensive maintenance instructions and materials	Product Code	HRC4002
Specie European Oak (Oak) Pattern 1-Strip Process Hand Textured Finish Oiled Profile PAR Edge Profile Square Edge Top Layer European Oak (Oak) Backing N/A (N/A) Thickness 4mm Width 100mm Length 300-1200mm Pack Size Grade Rustic Maintenance Comprehensive maintenance instructions and materials	Product Range	Vertical
Pattern 1-Strip Process Hand Textured Finish Oiled Profile PAR Edge Profile Square Edge Top Layer European Oak (Oak) Backing N/A (N/A) Thickness 4mm Width 100mm Length 300-1200mm Pack Size Grade Rustic Maintenance Comprehensive maintenance instructions and materials	Construction	Solid
Process Hand Textured Finish Oiled Profile PAR Edge Profile Square Edge Top Layer European Oak (Oak) Backing N/A (N/A) Thickness 4mm Width 100mm Length 300-1200mm Pack Size Grade Rustic Maintenance Comprehensive maintenance instructions and materials	Specie	European Oak (Oak)
Finish Oiled Profile PAR Edge Profile Square Edge Top Layer European Oak (Oak) Backing N/A (N/A) Thickness 4mm Width 100mm Length 300-1200mm Pack Size Grade Rustic Maintenance Comprehensive maintenance instructions and materials	Pattern	1-Strip
Profile PAR Edge Profile Square Edge Top Layer European Oak (Oak) Backing N/A (N/A) Thickness 4mm Width 100mm Length 300-1200mm Pack Size Grade Rustic Maintenance Comprehensive maintenance instructions and materials	Process	Hand Textured
Edge Profile Square Edge Top Layer European Oak (Oak) Backing N/A (N/A) Thickness 4mm Width 100mm Length 300-1200mm Pack Size Grade Rustic Maintenance Comprehensive maintenance instructions and materials	Finish	Oiled
Top Layer European Oak (Oak) Backing N/A (N/A) Thickness 4mm Width 100mm Length 300-1200mm Pack Size Grade Rustic Maintenance Comprehensive maintenance instructions and materials	Profile	PAR
Backing N/A (N/A) Thickness 4mm Width 100mm Length 300-1200mm Pack Size Grade Rustic Maintenance Comprehensive maintenance instructions and materials	Edge Profile	Square Edge
Thickness 4mm Width 100mm Length 300-1200mm Pack Size Grade Rustic Maintenance Comprehensive maintenance instructions and materials	Top Layer	European Oak (Oak)
Width 100mm Length 300-1200mm Pack Size Grade Rustic Maintenance Comprehensive maintenance instructions and materials	Backing	N/A (N/A)
Length 300-1200mm Pack Size Grade Rustic Maintenance Comprehensive maintenance instructions and materials	Thickness	4mm
Pack Size Grade Rustic Maintenance Comprehensive maintenance instructions and materials	Width	100mm
Grade Rustic Maintenance Comprehensive maintenance instructions and materials	Length	300-1200mm
Maintenance Comprehensive maintenance instructions and materials	Pack Size	
comprehensive manifestative most actions and materials	Grade	Rustic
	Maintenance	·

INSTALLATION METHODS

Fully Bonded	Yes* (recommended)
Nailed	Yes*
Floated on underlay	No
Over Underfloor Heating	No

GRADING CRITERIA

Known as either natural or rustic grade this allows a virtually limitless size and number of knots. Heartwood will be used, there will be colour variation, sapwood and filler; you should expect checks (cracks across the growth ring) and possibly some end shake (cracks between the rings). The colour of the filler is selected to compliment the wood rather than to match it exactly and it may vary from batch to batch.

N.B. The product grading criteria is inspected at each mill visually and should be taken as an approximation only. Please ask for further details

TECHNICAL CRITERIA

Origin	Europe
Responsible Certification	Please ask a member of staff for details
Janka Hardness Rating	1.120 lbf (4,980N)
Formaldehyde Emission	BDL (EN12149)
Pentachlorophenol Emission	NPD
Slip testing	Not assessed
Reaction to Fire Certification	Class E (EN13501-1)
Thermal Conductivity	NPD

INSTALLATION AND WARRANTY All Havwoods floor must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Havwoods warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standards worldwide.





^{*} Subject to compatible subfloor and correct installation (see Installation Guidelines) including sensors

^{**} This product may require on-site sanding prior to applying a suitable finish

[#] Temperature of top-face must never be allowed to exceed 27°C. UFH protocol to control temperature conditions is record;

‡ Pack lengths will either 1950mm or 2400mm dependant upon stock availability.