

TECHNICAL DATA SHEET

HRC4004 Bayou

Vertical

USAGE: (SEE HAVWOODS QUICK REFERENCE GUIDE TO CHOOSING THE CORRECT FLOOR).



PRODUCT DETAILS

Product Code	HRC4004	
Product Range	Vertical	
Construction	Solid	
Specie	European Oak (Oak)	
Pattern	1-Strip	
Process	Hand Textured	
Finish	Oiled	
Profile	PAR	
Edge Profile	Square Edge	
Top Layer	European Oak (Oak)	
Backing	N/A (N/A)	
Thickness	4mm	
Width	100mm	
Length	300-1200mm	
Pack Size		
Grade	Rustic	
Maintenance	Comprehensive maintenance instructions and materials are available from Havwoods for all floors.	

INSTALLATION METHODS

Fully Bonded	Yes* (recommended)
Nailed	Yes*
Floated on underlay	No
Over Underfloor Heating	No

GRADING CRITERIA

Known as either natural or rustic grade this allows a virtually limitless size and number of knots. Heartwood will be used, there will be colour variation, sapwood and filler; you should expect checks (cracks across the growth ring) and possibly some end shake (cracks between the rings). The colour of the filler is selected to compliment the wood rather than to match it exactly and it may vary from batch to batch.

N.B. The product grading criteria is inspected at each mill visually and should be taken as an approximation only. Please ask for further details

TECHNICAL CRITERIA

Origin	Furene
Origin	Europe
Responsible Certification	Please ask a member of staff for details
Janka Hardness Rating	1.120 lbf (4,980N)
Formaldehyde Emission	BDL (EN12149)
Pentachlorophenol Emission	NPD
Slip testing	Not assessed
Reaction to Fire Certification	Class E (EN13501-1)
Thermal Conductivity	NPD

INSTALLATION AND WARRANTY All Havwoods floor must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Havwoods warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standards worldwide.





^{*} Subject to compatible subfloor and correct installation (see Installation Guidelines) including sensors.

^{**} This product may require on-site sanding prior to applying a suitable finish

[#] Temperature of top-face must never be allowed to exceed 27°C. UFH protocol to control temperature conditions is reco ‡ Pack lengths will either 1950mm or 2400mm dependant upon stock availability.