

# **TECHNICAL DATA SHEET**

# CW1004 Lille

## Vertical

USAGE: (SEE HAVWOODS QUICK REFERENCE GUIDE TO CHOOSING THE CORRECT FLOOR).



### **PRODUCT DETAILS**

Product Code	CW1004
Product Range	Vertical
Construction	Solid
Specie	Cork (Quercus Suber)
Pattern	Tile
Process	Fine Sanded
Finish	Waxed
Profile	PAR
Edge Profile	Square Edge
Top Layer	Cork (Quercus Suber)
Backing	N/A (N/A)
Thickness	3mm
Width	300mm
Length	600mm
Pack Size	15.84m2
Grade	Natural
Maintenance	Comprehensive maintenance instructions and materials are available from Havwoods for all floors.

#### **INSTALLATION METHODS**

Fully Bonded	Yes* (recommended)
Nailed	No
Floated on underlay	No
Over Underfloor Heating	No

### **GRADING CRITERIA**

Veneered agglomerated cork tiles to be used as wallcoverings within buildings. Tiles are produced by gluing one decorative cork veneer with one backing of agglomerated cork. Tiles are cut in the dimensions of 600 x 300 mm and have a thickness of 3 mm. The surface is fine sanded and finished with wax.

N.B. The product grading criteria is inspected at each mill visually and should be taken as an approximation only. Please ask for further details

#### **TECHNICAL CRITERIA**

Origin	Europe
Responsible Certification	Please ask a member of staff for details
Janka Hardness Rating	1,200 lbf (5,340N)
Formaldehyde Emission	BDL (EN12149)
Pentachlorophenol Emission	NPD
Slip testing	Not assessed
Reaction to Fire Certification	Class F (EN13501-1)
Thermal Conductivity	NPD

INSTALLATION AND WARRANTY All Havwoods floor must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Havwoods warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standards worldwide.





<sup>\*</sup> Subject to compatible subfloor and correct installation (see Installation Guidelines) including sensors.

<sup>\*\*</sup> This product may require on-site sanding prior to applying a suitable finish

<sup>#</sup> Temperature of top-face must never be allowed to exceed 27°C. UFH protocol to control temperature conditions is record;

‡ Pack lengths will either 1950mm or 2400mm dependant upon stock availability.