

# **TECHNICAL DATA SHEET**

## HW7956 Novaya

## **Venture Plank**

USAGE: (SEE HAVWOODS QUICK REFERENCE GUIDE TO CHOOSING THE CORRECT FLOOR).



#### **INSTALLATION METHODS**

Glue Down	Yes* (recommended)
Nailed	No
Floated on underlay	No
Over Underfloor Heating	Yes*# (Please ask for our technical guidelines)

## **GRADING CRITERIA**

Typically, character grade will include both heartwood and sapwood and allows a wider range of colour variation. Knots are larger and you should expect checks (cracks across the growth ring). Filler will be use, the colour of which is selected to complement the wood rather than to match it exactly, and it may vary from batch to batch.

#### The above image is a finished product and should only be used as a design match

#### **PRODUCT DETAILS**

Product CodeHW7956Product RangeVenture PlankConstructionEngineeredSpecieEuropean OakPatternMansion WeaveProcessSandedFinishWhite UV OiledProfileTongue & GrooveEdge ProfileBevelled EdgeTop Layer4mm European OakBackingBirch PlywoodThickness15.5mm (5/8")Width190mm (7 1/2")Length289mm (11 3/8")Pack Size1.32m² (14.21ft²)GradeCharacterMaintenanceComprehensive maintenance instructions and materials are available from Havwoods for all floors.		
ConstructionEngineeredSpecieEuropean OakPatternMansion WeaveProcessSandedFinishWhite UV OiledProfileTongue & GrooveEdge ProfileBevelled EdgeTop Layer4mm European OakBackingBirch PlywoodThickness15.5mm (5/8")Width190mm (7 1/2")Length289mm (11 3/8")Pack Size1.32m² (14.21ft²)GradeCharacterMaintenanceComprehensive maintenance instructions and materials are available from Havwoods for all	Product Code	HW7956
SpecieEuropean OakPatternMansion WeaveProcessSandedFinishWhite UV OiledProfileTongue & GrooveEdge ProfileBevelled EdgeTop Layer4mm European OakBackingBirch PlywoodThickness15.5mm (5/8")Width190mm (7 1/2")Length289mm (11 3/8")Pack Size1.32m² (14.21ft²)GradeCharacterMaintenanceComprehensive maintenance instructions and materials are available from Havwoods for all	Product Range	Venture Plank
PatternMansion WeaveProcessSandedFinishWhite UV OiledProfileTongue & GrooveEdge ProfileBevelled EdgeTop Layer4mm European OakBackingBirch PlywoodThickness15.5mm (5/8")Width190mm (7 1/2")Length289mm (11 3/8")Pack Size1.32m² (14.21ft²)GradeCharacterMaintenanceComprehensive maintenance instructions and materials are available from Havwoods for all	Construction	Engineered
ProcessSandedFinishWhite UV OiledProfileTongue & GrooveEdge ProfileBevelled EdgeTop Layer4mm European OakBackingBirch PlywoodThickness15.5mm (5/8")Width190mm (7 1/2")Length289mm (11 3/8")Pack Size1.32m² (14.21ft²)GradeCharacterMaintenanceComprehensive maintenance instructions and materials are available from Havwoods for all	Specie	European Oak
FinishWhite UV OiledProfileTongue & GrooveEdge ProfileBevelled EdgeTop Layer4mm European OakBackingBirch PlywoodThickness15.5mm (5/8")Width190mm (7 1/2")Length289mm (11 3/8")Pack Size1.32m² (14.21ft²)GradeCharacterMaintenanceComprehensive maintenance instructions and materials are available from Havwoods for all	Pattern	Mansion Weave
ProfileTongue & GrooveEdge ProfileBevelled EdgeTop Layer4mm European OakBackingBirch PlywoodThickness15.5mm (5/8")Width190mm (7 1/2")Length289mm (11 3/8")Pack Size1.32m² (14.21ft²)GradeCharacterMaintenanceComprehensive maintenance instructions and materials are available from Havwoods for all	Process	Sanded
Edge Profile   Bevelled Edge     Top Layer   4mm European Oak     Backing   Birch Plywood     Thickness   15.5mm (5/8")     Width   190mm (7 1/2")     Length   289mm (11 3/8")     Pack Size   1.32m² (14.21ft²)     Grade   Character     Maintenance   Comprehensive maintenance instructions and materials are available from Havwoods for all	Finish	White UV Oiled
Top Layer   4mm European Oak     Backing   Birch Plywood     Thickness   15.5mm (5/8")     Width   190mm (7 1/2")     Length   289mm (11 3/8")     Pack Size   1.32m² (14.21ft²)     Grade   Character     Maintenance   Comprehensive maintenance instructions and materials are available from Havwoods for all	Profile	Tongue & Groove
BackingBirch PlywoodThickness15.5mm (5/8")Width190mm (7 1/2")Length289mm (11 3/8")Pack Size1.32m² (14.21ft²)GradeCharacterMaintenanceComprehensive maintenance instructions and materials are available from Havwoods for all	Edge Profile	Bevelled Edge
Thickness15.5mm (5/8")Width190mm (7 1/2")Length289mm (11 3/8")Pack Size1.32m² (14.21ft²)GradeCharacterMaintenanceComprehensive maintenance instructions and materials are available from Havwoods for all	Top Layer	4mm European Oak
Width   190mm (7 1/2")     Length   289mm (11 3/8")     Pack Size   1.32m² (14.21ft²)     Grade   Character     Maintenance   Comprehensive maintenance instructions and materials are available from Havwoods for all	Backing	Birch Plywood
Length 289mm (11 3/8")   Pack Size 1.32m² (14.21ft²)   Grade Character   Maintenance Comprehensive maintenance instructions and materials are available from Havwoods for all	Thickness	15.5mm (5/8")
Pack Size   1.32m² (14.21ft²)     Grade   Character     Maintenance   Comprehensive maintenance instructions and materials are available from Havwoods for all	Width	190mm (7 1/2")
Grade     Character       Maintenance     Comprehensive maintenance instructions and materials are available from Havwoods for all	Length	289mm (11 3/8")
Maintenance     Comprehensive maintenance instructions and materials are available from Havwoods for all	Pack Size	1.32m² (14.21ft²)
materials are available from Havwoods for all	Grade	Character
	Maintenance	materials are available from Havwoods for all

#### N.B. The product grading criteria is inspected at each mill visually and should be taken as an approximation only. Please ask for further details

## **TECHNICAL CRITERIA**

<b>Responsible Certification</b>	Please ask a member of staff for details
Janka Hardness Rating	1,120 lbf (4,980N)
Formaldehyde Emission	BLQ ppm - TSCA VI Compliant
Slip testing	71/29 PTV (CEN/TS 15676:2007)
Critical Radiant Flux	Class I - ASTM E 648
Thermal Conductivity	λ 0.13 W/m K (EN 12664)



\* Subject to compatible subfloor and correct installation (see Installation Guidelines) including sensors

 $\space{1.5}$  \*\* This product may require on-site sanding prior to applying a suitable finish

# Temperature of top-face must never be allowed to exceed 27°c/80°F. UFH protocol to control temperature conditions is recommended.

 $\ddagger$  Pack lengths will vary between 1950mm or 2400mm dependant upon stock availability.

#### INSTALLATION AND WARRANTY

All Havwoods floors must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Havwoods warranty will apply only to floors which have been installed by a competent flooring installer comparable to NWFA standards or equivalent standards worldwide.

© This technical data sheet was written by Havwoods International. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this sheet are intended only as illustrations. No rights can be derived from them.

Havwoods International (North America); 151 W 18th St, New York, NY 1011, USA Tel: 1 844 808 9663 (WOOD) Info@havwoodsusa.com