

Technical Data Sheet

HW31018 Brienne PurePanel

Usage: See Havwoods quick reference guide to choosing the correct floor



Installation Methods

| | |
|--------------|-----|
| Fully Bonded | Yes |
| Screwed | No |

Grading Criteria

- Endless opportunities across a multitude of applications.
- Seven of Havwoods' most popular on-trend colours.
- Mix-match production technique ensures each panel is consistent in colour and quality.
- Panels are supplied ready to use and require no additional finishing on-site.
- Our pre-finished panels make installation and fabrication effortless.
- Simply cut and use our matching PureEdge as required.

N.B. The product grading criteria is inspected at each mill visually and should be taken as an approximation only. Please ask for further details

Product Details

| | |
|---------------|--|
| Product Code | HW31018 |
| Product Range | PurePanel |
| Construction | Composite MDF |
| Specie | European Oak Veneer (Quercus spp.) |
| Pattern | Veneered Panel |
| Process | Brushed & Stained |
| Finish | Matt Lacquered |
| Profile | PAR |
| Edge Profile | Square Edge |
| Top Layer | 0.6mm European Oak (Quercus spp.) |
| Backing | MDF (Reconstituted Veneer) |
| Thickness | 19mm |
| Width | 1220mm |
| Length | 3050mm |
| Pack Size | 3.78m ² |
| Maintenance | Comprehensive maintenance instructions and materials are available from Havwoods for all floors. |

Technical Criteria

| | |
|--------------------------------|------------------------------|
| Origin | Belgium |
| Responsible Certification | FSC® Certified (FSC-C009500) |
| Formaldehyde Emission | E1 (EN 717-1/2) |
| Pentachlorophenol Emission | PCP Free |
| Reaction to Fire Certification | Dfl-s1-d0 |
| Thermal Conductivity | 0.11 W/mK |



The mark of responsible forestry

^ Please note that this is a smoked/fumed product. This reactive process will typically generate a wider range of colour variation in the product.

* Subject to compatible subfloor and correct installation (see Installation Guidelines) including sensors.

** This product may require on-site sanding prior to applying a suitable finish

Temperature of top-face must never be allowed to exceed 27°C. UFH protocol to control temperature conditions is recommended.

‡ Pack lengths will either 1950mm or 2400mm dependant upon stock availability.

Installation and Warranty: All Havwoods floor must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Havwoods warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standards worldwide.

This technical data sheet was written by Havwoods International. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs use in the sheet are intended only as illustrations. No rights can be derived from them.



Havwoods Limited, Carnforth Business Park, Oakwood Way,
Carnforth, Lancashire LA5 9FD

Tel: +44 (0)1524 737 000; Fax: +44 (0)1524 737 001
info@havwoods.com
www.havwoods.com