

TECHNICAL DATA SHEET

HW820 Proteus

Boutique

USAGE: (SEE HAVWOODS QUICK REFERENCE GUIDE TO CHOOSING THE CORRECT FLOOR).



INSTALLATION METHODS

Fully Bonded	Yes*
Nailed	No
Floated on underlay	Yes*
Over Underfloor Heating	Yes*# (Please ask for our technical guidelines)

GRADING CRITERIA

Typically, character grade will include both heartwood and sapwood and allows a wider range of colour variation. Knots are larger and you should expect checks (cracks across the growth ring). The colour of the filler is intended to complement the natural structure of the wood, where features such as knots are in contrast to the surrounding timber, and it may vary from batch to batch.

N.B. The product grading criteria is inspected at each mill visually and should be taken as an approximation only. Please ask for further details

PRODUCT DETAILS

Product Code	HW820	
Product Range	Boutique	
Construction	Engineered	
Specie	European Oak(Quercus Robur)	
Pattern	1-Strip	
Process	Sanded	
Finish	Matt Lacquered	
Profile	Click system	
Edge Profile	Bevelled	
Top Layer	0.6mm European Oak(Quercus Robur)	
Backing	10.4mm HDF	
Thickness	11mm	
Width	273mm	
Length	2379mm (May include up to 25% shorter boards)	
Pack Size	2.12m2	
Grade	Character	
Maintenance	Comprehensive maintenance instructions and materials are available from Havwoods for all floors.	

TECHNICAL CRITERIA

Origin	Europe	
Responsible Certification	FSC [®] Certified (FSC-C009500)	
Janka Hardness Rating	1,120 lbf (4,980N)	
Formaldehyde Emission	E1 (EN717-1)	
Pentachlorophenol Emission	< 5ppm (CEN/TR 14823)	
Slip testing	95/39 PTV (CEN/TS 15676)	
Reaction to Fire Certification	Bfl-s1 (EN13501-1)	
Thermal Conductivity	< 0.16 W/m K	

* Subject to compatible subfloor and correct installation (see Installation Guidelines) including sensors

** This product may require on-site sanding prior to applying a suitable finish

Temperature of top-face must never be allowed to exceed 27°C. UFH protocol to control temperature conditions is rec ‡ Pack lengths will either 1950mm or 2400mm dependant upon stock availability.

INSTALLATION AND WARRANTY All Havwoods floor must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Hawwoods warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standards worldwide.

This technical data sheet was written by Havwoods International. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs use in the sheet are intended only as illustrations. No rights can be derived from them.



Havwoods International, Carriforth Business Park, Oakwood Way, Carnforth, Lancashire LAS 9FD; Tel - +44 (0)1524 737 000; Fax - +44 (0)1524 737 001; info@havwoods.com www.havwoods.com