

TECHNICAL DATA SHEET

HW3755H Heres

Boutique

USAGE: (SEE HAVWOODS QUICK REFERENCE GUIDE TO CHOOSING THE CORRECT FLOOR).



INSTALLATION METHODS

Fully Bonded	Yes* (recommended)
Nailed	Yes*
Floated on underlay	No
Over Underfloor Heating	Yes*# (water-fed systems only)

GRADING CRITERIA

Known as either natural or rustic grade this allows a virtually limitless size and number of knots. Heartwood will be used, there will be colour variation, sapwood and filler; you should expect checks (cracks across the growth ring) and possibly some end shake (cracks between the rings). The colour of the filler is intended to complement the natural structure of the wood, where features such as knots are in contrast to the surrounding timber, and it may vary from batch to batch. oduct grading criteria is inspected at each mill visually and should be taken as an approximation only. Please ask N.B. The product for further detail

PRODUCT DETAILS

Product Code	HW3755H	
Product Range	Boutique	
Construction	Engineered	
Specie	European Oak(Quercus Robur)	
Pattern	1-Strip	
Process	Smoked	
Finish	UV Oiled	
Profile	Tongue & Groove	
Edge Profile	4-Sided Bevelled Edge	
Top Layer	6mm European Oak(Quercus Robur)	
Backing	Birch Plywood(Hevea)	
Thickness	22mm (7/8")	
Width	240mm (9 1/2")	
Length	2450mm (96 1/2")	
Pack Size	2.35m ²	
Grade	Rustic	
Maintenance	Comprehensive maintenance instructions and materials are available from Havwoods for all floors.	

TECHNICAL CRITERIA

Origin	Europe
Responsible Certification	Please ask a member of staff for details
Janka Hardness Rating	1,120 lbf (4,980N)
Formaldehyde Emission	NPD
Slip testing	NPD
Critical Radiant Flux	NPD
Thermal Conductivity	NPD



* Subject to compatible subfloor and correct installation (see Installation Guidelines) including sensors

** This product may require on-site sanding prior to applying a suitable finish

Temperature of top-face must never be allowed to exceed 27*C. UFH protocol to control temperature conditions is reco ‡ Pack lengths will either 1950mm or 2400mm dependant upon stock availability.

INSTALLATION AND WARRANTY All Havwoods floors must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Hawwoods warrenty will apply only to floors which have been installed by a competent flooring installer comparable to NWFA standards or equivalent standards worldwide.

This technical data sheet was written by Hawwoods International. At the time of writing and publiciation of the sheet, all informatic is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs use in the sheet are intended only as illustrations. No rights can be derived from them.