



TECHNICAL DATA SHEET

HR002 European Oak

The Raw Collection

USAGE: (SEE HAVWOODS QUICK REFERENCE GUIDE TO CHOOSING THE CORRECT FLOOR).



PRODUCT DETAILS

Product Code	HR002
Product Range	The Raw Collection
Construction	Engineered
Specie	European Oak(Quercus Robur)
Pattern	1-Strip
Process	Sanding required
Finish	Unfinished
Profile	Tongue & Groove
Edge Profile	2-Sided Beveled Edge
Top Layer	6mm European Oak(Quercus Robur)
Backing	Birch(Betula spp.)
Thickness	20mm (3/4")
Width	180mm (7 1/8")
Length	2000-3000mm (78 3/4" - 118 1/8")
Pack Size	TBC
Grade	Rustic
Maintenance	Comprehensive maintenance instructions and materials are available from Havwoods for all floors.

INSTALLATION METHODS

Fully Bonded	Yes* (recommended)
Nailed	Yes*
Floated on underlay	Yes*
Over Underfloor Heating	Yes*# (Please ask for our technical guidelines)

GRADING CRITERIA

Known as either natural or rustic grade this allows a virtually limitless size and number of knots. Heartwood will be used, there will be colour variation, sapwood and filler; you should expect checks (cracks across the growth ring) and possibly some end shake (cracks between the rings). The colour of the filler is intended to complement the natural structure of the wood, where features such as knots are in contrast to the surrounding timber, and it may vary from batch to batch.

N.B. The product grading criteria is inspected at each mill visually and should be taken as an approximation only. Please ask for further details

TECHNICAL CRITERIA

Origin	Netherlands
Responsible Certification	Please ask a member of staff for details
Janka Hardness Rating	1.120 lbf (4,980N)
Formaldehyde Emission	NPD
Slip testing	NPD
Critical Radiant Flux	NPD
Thermal Conductivity	NPD



* Subject to compatible subfloor and correct installation (see Installation Guidelines) including sensors.

** This product may require on-site sanding prior to applying a suitable finish

Temperature of top-face must never be allowed to exceed 27°C. UFH protocol to control temperature conditions is recommended.

‡ Pack lengths will either 1950mm or 2400mm dependant upon stock availability.

INSTALLATION AND WARRANTY All Havwoods floors must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Havwoods warranty will apply only to floors which have been installed by a competent flooring installer comparable to NWFA standards or equivalent standards worldwide.

This technical data sheet was written by Havwoods International. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs use in the sheet are intended only as illustrations. No rights can be derived from them.