

# **TECHNICAL DATA SHEET**

# **HRC1905 Notus**

## **Vertical**

USAGE: (SEE HAVWOODS QUICK REFERENCE GUIDE TO CHOOSING THE CORRECT FLOOR).



#### **PRODUCT DETAILS**

Product Code	HRC1905	
Product Range	Vertical	
Construction	Solid	
Specie	American Pine(Hemlock/Pine)	
Pattern	1-Strip	
Process	Weathered	
Finish	Unfinished	
Profile	PAR	
Edge Profile	Reclaimed Edge	
Top Layer	Pine(Hemlock/Pine)	
Backing	N/A(N/A)	
Thickness	19mm (3/4")	
Width	115-290mm (4 1/2" - 11 3/8")	
Length	Random (Random)	
Pack Size	TBC	
Grade	Rustic	
Maintenance	Comprehensive maintenance instructions and materials are available from Havwoods for all floors.	

#### **INSTALLATION METHODS**

Fully Bonded	Yes* (recommended)
Nailed	Yes*
Floated on underlay	No
Over Underfloor Heating	No

#### **GRADING CRITERIA**

Known as either natural or rustic grade this allows a virtually limitless size and number of knots. Heartwood will be used, there will be colour variation, sapwood and filler; you should expect checks (cracks across the growth ring) and possibly some end shake (cracks between the rings). The colour of the filler is intended to complement the natural structure of the wood, where features such as knots are in contrast to the surrounding timber, and it may vary from batch to batch.

oduct grading criteria is inspected at each mill visually and should be taken as an approximation only. Please ask

### **TECHNICAL CRITERIA**

Origin	USA
Responsible Certification	FSC® Certified (FSC-C009500)
Janka Hardness Rating	540 lbf (2,420N)
Formaldehyde Emission	BLQ ppm - TSCA VI Compliant
Slip testing	Not assessed
Critical Radiant Flux	NPD
Thermal Conductivity	NPD





INSTALLATION AND WARRANTY All Havwoods floors must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Havwoods warrenty will apply only to floors which have been installed by a competent flooring installer comparable to NWFA standards or equivalent standards worldwide.

<sup>\*\*</sup> This product may require on-site sanding prior to applying a suitable finish

<sup>#</sup> Temperature of top-face must never be allowed to exceed 27°C. UFH protocol to control temperature conditions is reco

<sup>‡</sup> Pack lengths will either 1950mm or 2400mm dependant upon stock availability.