



TECHNICAL DATA SHEET

HW16859 Columba - Plank

Boutique

USAGE: (SEE HAVWOODS QUICK REFERENCE GUIDE TO CHOOSING THE CORRECT FLOOR).



PRODUCT DETAILS

| | |
|---------------|--|
| Product Code | HW16859 |
| Product Range | Boutique |
| Construction | Engineered |
| Specie | European Oak(Quercus Robur) |
| Pattern | 1-Strip |
| Process | Brushed |
| Finish | UV Oiled |
| Profile | Tongue & Groove |
| Edge Profile | Bevelled Edge |
| Top Layer | 3mm European Oak(Quercus Robur) |
| Backing | Birch(Betula spp.) |
| Thickness | 9mm |
| Width | 120mm |
| Length | 800-1400mm (May include up to 25% shorter boards) |
| Pack Size | 1.44m ² |
| Grade | Character |
| Maintenance | Comprehensive maintenance instructions and materials are available from Havwoods for all floors. |

INSTALLATION METHODS

| | |
|-------------------------|---|
| Fully Bonded | Yes* (recommended) |
| Nailed | No |
| Floated on underlay | No |
| Over Underfloor Heating | Yes*# (Please ask for our technical guidelines) |

GRADING CRITERIA

Typically, character grade will include both heartwood and sapwood and allows a wider range of colour variation. Knots are larger and you should expect checks (cracks across the growth ring). The colour of the filler is intended to complement the natural structure of the wood, where features such as knots are in contrast to the surrounding timber, and it may vary from batch to batch.

N.B. The product grading criteria is inspected at each mill visually and should be taken as an approximation only. Please ask for further details

TECHNICAL CRITERIA

| | |
|--------------------------------|------------------------------|
| Origin | Europe |
| Responsible Certification | FSC® Certified (FSC-C009500) |
| Janka Hardness Rating | 1,120 lbf (4,980N) |
| Formaldehyde Emission | E1 (EN 717-1:2006) |
| Pentachlorophenol Emission | < 5ppm (CEN/TR 14823) |
| Slip testing | 65/41 PTV (BS7976-2) |
| Reaction to Fire Certification | Cfl-s1 (EN 13501-1) |
| Thermal Conductivity | λ 0.09 W/m K (EN 12664) |

* Subject to compatible subfloor and correct installation (see Installation Guidelines) including sensors.

** This product may require on-site sanding prior to applying a suitable finish

Temperature of top-face must never be allowed to exceed 27°C. UFH protocol to control temperature conditions is recommended.

‡ Pack lengths will either 1950mm or 2400mm dependant upon stock availability.

INSTALLATION AND WARRANTY All Havwoods floor must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Havwoods warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standards worldwide.

This technical data sheet was written by Havwoods International. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs use in the sheet are intended only as illustrations. No rights can be derived from them.

