

TECHNICAL DATA SHEET

HW3008 AMAZON HERRINGBONE

VENTURE PLANK

USAGE: SEE HAVWOODS QUICK REFERENCE GUIDE TO CHOOSING THE CORRECT FLOOR.



The photographs used in this sheet are intended only as illustrations, colours shown are only as accurate as the printing process or device screen will allow. Due to the size of this photograph, it does not provide any indication of grading. Please refer to our separate grading rules. No rights can be derived from them.

PRODUCT DETAILS

Product Code	HW3008
Product Range	Venture Plank
Construction	Engineered
Species	European Oak
Pattern	Herringbone
Process	Sanded
Finish	White UV Oiled
Profile	Tongue & Groove
Edge Profile	4-Sided Bevelled Edge
Top Layer	4mm European Oak
Backing	Birch Plywood
Thickness	13mm
Width	120mm
Length	600mm
Grade	Prime
Maintenance	Comprehensive maintenance instructions and materials are available from Havwoods Ltd. for all floors. Contact your Havwoods consultant on 1300 428 966.

INSTALLATION METHODS

Fully Bonded	Yes* (recommended)
Nailed	No
Floated on underlay	No
Over Underfloor Heating	Yes*# (Please ask for our technical guidelines)

GRADING CRITERIA

Typically, prime grade has few, if any knots, and these will be of minimal size. There will also be a minimal amount of sapwood and filler, if any at all. Where filler is used its colour is selected to complement the wood rather than to match it exactly and the colour of the filler may vary from batch to batch. There will be a relatively small amount of colour variation in the timber itself.

NB: The product grading criteria is an approximation only. Please ask for details. Contact your Havwoods consultant on 1300 428 966.

TECHNICAL CRITERIA

Origin	Europe
Sustainability	Cradle to Cradle™
Janka Hardness Rating	1,120 lbf (4,980N)
Formaldehyde Emission	E1(EN 717-1)
Pentachlorophenol Emission	< 5ppm (CEN/TR 14823)
Slip Testing	65/39 PTV (BS7976-2:2002+A1:2013)
European reaction to fire classification	Cfl-s1 (EN13501-1)
Thermal Conductivity	0.17 W/m K (EN 12664)

* Subject to compatible subfloor and correct installation (see Installation Guidelines) including sensors.

** This product may require on-site sanding prior to applying a suitable finish

Temperature of top-face must never be allowed to exceed 27° C. Under Floor Heating (UFH) protocol to control temperature conditions is recommended.

INSTALLATION AND WARRANTY

All Havwoods floors must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Havwoods warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standard worldwide.

© This technical data sheet was written by Havwoods Limited, Carnforth Business Park, Oakwood Way, Carnforth Lancashire LA5 9FD. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this sheet are intended only as illustrations, colours shown are only as accurate as the printing process or device screen will allow. No rights can be derived from them.

HAVWOODS BRISBANE SHOWROOM

2/36 Doggett Street
Newstead, QLD 4006

HAVWOODS SYDNEY SHOWROOM

28 Margaret Street
Sydney CBD, NSW 2000

HAVWOODS MELBOURNE SHOWROOM

9-11 Claremont Street
South Yarra VIC 3141

HAVWOODS NEWCASTLE SHOWROOM

150 King Street
Newcastle, NSW 2300

1300 428 966 | info@havwoods.com.au
www.havwoods.com.au

