

Technical Data Sheet

HW33014 Paron

PureVeneer

Usage: See Havwoods quick reference guide to choosing the correct floor



Installation Methods	
Fully Bonded	Yes
Screwed	No

Grading Criteria

- Endless opportunities across a multitude of applications.
 Seven of Havwoods' most popular on-trend colours.
 Mix-match production technique ensures each panel is consistent in colour and quality.
 Panels are supplied ready to use and require no additional finishing on-site.
 Our pre-finished panels make installation and fabrication effortless.

- Simply cut and use our matching PureEdge as required.

N.B. The product grading criteria is inspected at each mill visually and should be taken as an approximation only. Please ask for further details


Product Details	
Product Code	HW33014
Product Range	PureVeneer
Construction	Solid Veneer
Specie	European Oak Veneer (Quercus spp.)
Pattern	Veneered Sheet
Process	Brushed & Stained
Finish	Matt Lacquered
Profile	PAR
Edge Profile	Square Edge
Top Layer	0.6mm European Oak (Quercus spp.)
Backing	High Pressure Laminte (HPL)
Thickness	1mm
Width	1220mm
Length	3050mm
Pack Size	3.78m²
Maintenance	Comprehensive maintenance instructions and materials are available from Havwoods for all floors.

Technical Criteria	
Origin	Belgium
Responsible Certification	FSC® Certified (FSC-C009500)
Formaldehyde Emission	E1 (EN 717-1/2)
Pentachlorophenol Emission	PCP Free
Reaction to Fire Certification	Dfl-s1-d0
Thermal Conductivity	NPD



† Pack lengths will either 1950mm or 2400mm dependant upon stock availability.

Installation and Warranty: All Havwoods floor must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Havwoods warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standards worldwide.







Havwoods Limited, Carnforth Business Park, Oakwood Way,

Tel: +44 (0)1524 737 000; Fax: +44 (0)1524 737 001 info@havwoods.com www.havwoods.com

[^] Please note that this is a smoked/furned product. This reactive process will typically generate a wider range of colour variation in the product.

 $^{{}^{\}star}\operatorname{Subject} \ \text{to compatible subfloor and correct installation (see Installation Guidelines) including sensors.}$

^{**} This product may require on-site sanding prior to applying a suitable finish

[#] Temperature of top-face must never be allowed to exceed 27°C. UFH protocol to control temperature conditions is recommended.