

## **Technical Data Sheet**

## HW240301 Simplista M3 **Simplista**

Usage: See Havwoods quick reference guide to choosing the correct floor



| Fully Bonded              | Yes*                                     |
|---------------------------|--|
| Screwed                   | Yes*                                     |
|                           |  |
|                           |  |
| Technical Criteria        |  |
| Origin                    | Europe                                   |
| Responsible Certification | Please ask a member of staff for details |
|                           |  |
|                           |  |

Installation Methods

| Product Details |  |
|-----------------|--|
| Product Code    | HW240301   |
| Product Range   | Simplista  |
| Construction    | Milled MDF   |
| Finish          | Unfinished   |
| Profile         | PAR  |
| Edge Profile    | Square Edge  |
| Thickness       | 6mm  |
| Width           | 1200mm   |
| Length          | 2400mm   |
| Pack Size       | TBC  |
| Maintenance     | Comprehensive maintenance instructions and materials are available from Havwoods for all floors. |

\* Peack lengths will either 1950mm or 2400mm dependant upon stock availability.

Installation and Warranty: All Havwoods floor must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Havwoods warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standards worldwide.

This technical data sheet was written by Hawwoods International. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs use in the sheet are intended only as illustrations. No rights can be derived from them.





Havwoods Limited, Carnforth Business Park, Oakwood Way, Carnforth, Lancashire LA5 9FD

<sup>^</sup> Please note that this is a smoked/fumed product. This reactive process will typically generate a wider range of colour variation in the product.

<sup>\*</sup> Subject to compatible subfloor and correct installation (see Installation Guidelines) including sensors.

\*\* This product may require on-site sanding prior to applying a suitable finish

# Temperature of top-face must never be allowed to exceed 27°C. UFH protocol to control temperature conditions is recommended.