

Technical Data Sheet

HW6510 Walnut Parisienne Venture Plank

Usage: See Havwoods quick reference guide to choosing the correct floor



Installation Methods

Fully Bonded	Yes* (recommended)
Nailed	No
Floated on underlay	No
Over Underfloor Heating	Yes*# (Please ask for our technical guidelines)

Grading Criteria

Known as either select or classic grade, typically this will have a mix of almost prime boards with other planks which have more knots. Slightly larger knots are allowed in this grade. Heartwood and colour variation in the timber should be expected and there may be some checks (cracks across the growth ring), sapwood and filler. The colour of the filler is intended to complement the natural structure of the wood, where features such as knots are in contrast to the surrounding timber, and it may vary from batch to batch.

N.B. The product grading criteria is inspected at each mill visually and should be taken as an approximation only. Please ask for further details

Product Details

Product Code	HW6510
Product Range	Venture Plank
Construction	Multi Layered Engineered
Specie	American Black Walnut (<i>Juglans Nigra</i>)
Pattern	1-Strip
Process	Sanded
Finish	Lacquered
Profile	Tongue & Groove
Edge Profile	Bevelled Edge
Top Layer	3.5mm American Black Walnut (<i>Juglans Nigra</i>)
Backing	Birch Plywood (<i>Betula</i> spp.)
Thickness	18mm
Width	180mm
Length	800-2400mm (May include up to 25% shorter boards)
Pack Size	TBC
Grade	Select
Maintenance	Comprehensive maintenance instructions and materials are available from Havwoods for all floors.

Technical Criteria

Origin	Europe
Responsible Certification	Please ask a member of staff for details
Janka Hardness Rating	1,010 lbf (4,490 N)
Formaldehyde Emission	E1 (EN717-1)
Pentachlorophenol Emission	< 5ppm (CEN/TR 14823)
Slip testing	USRV 56 (CEN/TS 15676:2007-11)
Reaction to Fire Certification	Cfl-s1 (EN 13501-1:2018-12)
Thermal Conductivity	λ 0.14 W/m K (EN 12664:2001)

[^] Please note that this is a smoked/fumed product. This reactive process will typically generate a wider range of colour variation in the product.

^{*} Subject to compatible subfloor and correct installation (see Installation Guidelines) including sensors.

^{**} This product may require on-site sanding prior to applying a suitable finish

[#] Temperature of top-face must never be allowed to exceed 27°C. UFH protocol to control temperature conditions is recommended.

[‡] Pack lengths will either 1950mm or 2400mm dependant upon stock availability.

Installation and Warranty: All Havwoods floor must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Havwoods warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standards worldwide.

This technical data sheet was written by Havwoods International. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs use in the sheet are intended only as illustrations. No rights can be derived from them.



Havwoods Limited, Carnforth Business Park, Oakwood Way,
Carnforth, Lancashire LA5 9FD

Tel: +44 (0)1524 737 000; Fax: +44 (0)1524 737 001
info@havwoods.com
www.havwoods.com