# (H) HAVWOODS

### **Technical Data Sheet**

## **Elegante Veneer Costato** Pre-glued non-woven fabric TNT

Usage: See Havwoods quick reference guide to choosing the correct floor

| Products       |   |
|----------------|---|
| Costato W3M5   | 5mm Mills Spacing<br>3mm Total ^<br>Thickness 0.3mm TNT Backing       |
| Costato W3M7.5 | 7.5mm Mills Spacing<br>3mm Total<br>Thickness<br>0.3mm TNT Backing    |
| Costato W3M10  | 10mm Mills Spacing<br>3mm Total —<br>Thickness —<br>0.3mm TNT Backing |
| Costato W6M10  | 10mm Mills Spacing<br>6mm Total —[<br>Thickness<br>0.3mm TNT Backing  |
| Costato W6M13  | 6mm Total — 13mm Mills Spacing<br>Thickness — 0.3mm TNT Backing       |
| Costato W6M20  | 20mm Mills Spacing<br>6mm Total – [<br>Thickness<br>0.3mm TNT Backing |

# Available Colours Makassar American walnut Ebony Grey oak Teak Light grey Light American walnut Gabon ebony Rosewood Thermo oak

Please ask a member of staff for more details about our available colours

### **Product Details**

| Pattern      | Ribbed                           |
|--------------|----------------------------------|
| Specie       | Ayous (Triplochiton scleroxylon) |
| Finish       | Unfinished                       |
| Profile      | PAR                              |
| Edge Profile | Square Edge                      |
| Dimensions   | 3130x1220mm                      |

#### **Technical Criteria**

Origin Janka Hardness Rating

Europe 430 lbf (1,910N)



^ Please note that this is a smoked/fumed product. This reactive process will typically generate a wider range of colour variation in the product. \* Subject to compatible subfloor and correct installation (see Installation Guidelines) including sensors.

\*\* This product may require on-site sanding prior to applying a suitable finish

5-FEBRUARY-2024/NA

# Temperature of top-face must never be allowed to exceed 27°C. UFH protocol to control temperature conditions is recommended. ‡ Pack lengths will either 1950mm or 2400mm dependant upon stock availability.

Installation and Warranty: All Havwoods floor must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Havwoods warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standards worldwide.

This technical data sheet was written by Hawwoods International. At the time of writing and publiciation of the sheet, al information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs use in the sheet are intended only as illustrations. No rights can be derived from them.



Havwoods International (North America) 151 W 18th St, New York, NY 1011, USA

Tel - 1 884 808 9663 (WOOD) info@havwoodsusa.com www.havwoodsusa.com