


## Technical Data Sheet

### EP148 Spotted Gum Herringbone

#### Australian Collection

Usage: See Havwoods Quick Reference guide to choosing the correct floor.



The photographs used in this sheet are intended only as illustrations, colours shown are only as accurate as the printing process or device screen will allow. Due to the size of this photograph, it does not provide any indication of grading. Please refer to our separate grading rules. No rights can be derived from them.

#### Product Details

Product Code	EP148
Product Range	Australian Collection
Construction	Engineered
Species	Australian Spotted Gum
Pattern	Herringbone
Process	Sanded
Finish	Matt Lacquered
Profile	Tongue and groove
Edge Profile	Bevelled Edge
Top Layer	3mm Spotted Gum Lamella
Backing	Hevea Core, Eucalyptus Backing
Thickness	14mm
Width	136mm
Length	680mm
Grade	Classic
Maintenance	Comprehensive maintenance instructions and materials are available from Havwoods Ltd. for all floors. Contact your Havwoods consultant on 1300 428 966.

\* Subject to compatible subfloor and correct installation (see Installation Guidelines) including sensors.

\*\* This product may require on-site sanding prior to applying a suitable finish

# Temperature of top-face must never be allowed to exceed 27°C. Under Floor Heating (UFH) protocol to control temperature conditions is recommended.

#### Installation and Warranty

All Havwoods floors must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Havwoods warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standard worldwide.

© This technical data sheet was written by Havwoods Limited, Carnforth Business Park, Oakwood Way, Carnforth Lancashire LA5 9FD. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this sheet are intended only as illustrations, colours shown are only as accurate as the printing process or device screen will allow. No rights can be derived from them.

#### Installation Methods

Fully Bonded	Yes*
Nailed	No
Floated on underlay	Yes*
Over Underfloor Heating	Not Recommended

#### Grading Criteria

Classic grade typically will include both heartwood and sapwood and allows a wider range of colour variation ranging from pale grey and light brown to a dark chocolate with some reddish tinges. Timber colours are mainly dependent on the wood species. All timber varies in colour when exposed to light over a period of time. Knots are larger and you should expect checks (cracks across the growth ring). Filler will be used, the colour of which is carefully selected to complement the wood rather than to match it exactly. Colour of filler used may vary from batch to batch. Pin holes are allowed. Gum veins are allowed - width up to 5mm permitted and individual gum vein up to 60% of the board length permitted.

NB: The product grading criteria is an approximation only. Please ask for details. Contact your Havwoods consultant on 1300 428 966.

#### Technical Criteria

Origin	Australian grown lamella, manufactured in Malaysia
Sustainability	Havwoods timber is sourced from sustainably managed forests that also adhere to local illegal logging legislation.
Janka Hardness Rating	11 kN
Slip Testing	P3 - Slip report available

**Havwoods Brisbane Showroom**  
2/36 Doggett Street  
Newstead, QLD 4006

**Havwoods Sydney Showroom**  
28 Margaret Street  
Sydney CBD, NSW 2000

**Havwoods Melbourne Showroom**  
9-11 Claremont Street  
South Yarra VIC 3141

**Havwoods Newcastle Showroom**  
150 King Street  
Newcastle, NSW 2300

1300 428 966 | [info@havwoods.com.au](mailto:info@havwoods.com.au)  
[www.havwoods.com.au](http://www.havwoods.com.au)

